

Entry Date	02/13/2003
Update Date	04/06/2010
Received Date	

Well Name	Township	Range	Dir	Section	Subsection	Well Depth	Depth Completed	Date Well Completed
	33	22	W	4	BCCBCB	64 ft.	64 ft.	11/10/2002
Elevation	920 ft.	Elev. Method	7.5 minute topographic map (+/- 5 feet)					
Address								
Well 22571 TYPO CREEK DR NE LINWOOD TOWNSHIP MN								
Stratigraphy Information								
Geological Material	From	To (ft.)	Color	Hardness				
SAND	0	15	BROWN	SOFT				
SAND & CLAY	15	55	GRAY	MEDIUM				
SAND	55	64	RED	SOFT				
Use domestic Status Active								
Well Hydrofractured? Yes ☐ No ☐ From To								
Casing Type Single casing Joint Threaded								
Drive Shoe? Yes ☒ No ☐ Above/Below								
Casing Diameter Weight								
4 in. To 64 ft. 11 lbs./ft.								
Open Hole From ft. To ft.								
Screen? ☒ Type stainless Make JOHNSON								
Diameter Slot/Gauze Length Set								
2 in. 18 48 ft. 60 ft. 64 ft.								
Static Water Level								
25 ft. land surface Measure 11/10/2002								
Pumping Level (below land surface)								
30 ft. 2 hrs. Pumping at 10 g.p.m.								
Wellhead Completion								
Pitless adapter manufacturer SNIPY Model 4IN								
☐ Casing Protection ☐ 12 in. above grade								
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified								
Material Amount From To								
bentonite 1 Sacks 0 ft. 30 ft.								
Nearest Known Source of Contamination								
80 feet East Direction Septic tank/drain field Type								
Well disinfected upon completion? ☒ Yes ☐ No								
Pump ☐ Not Installed Date Installed 11/10/2002								
Manufacturer's name STA RITE								
Model Number HP 0.5 Volt 220								
Length of drop pipe 50 ft Capacity 10 g.p. Typ Submersible								
Abandoned								
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No								
Variance								
Was a variance granted from the MDH for this well? ☐ Yes ☒ No								
Miscellaneous								
First Bedrock Aquifer Quat. buried								
Last Strat sand-red Depth to Bedrock ft								
Located by Minnesota Geological Survey								
Locate Method GPS SA Off (averaged) (15 meters)								
System UTM - NAD83, Zone 15, Meters X 492135 Y 5025038								
Unique Number Verification Address verification Input Date 03/01/2010								
Angled Drill Hole								
Well Contractor								
Anderson A. Well 13093 ANDERSON, A.								
Licensee Business Lic. or Reg. No. Name of Driller								
Minnesota Well Index Report						596566		
						Printed on 08/13/2026 HE-01205-15		