

601183

County Hubbard
Quad Benedict
Quad ID 277B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 09/24/1998
Update Date 06/22/2016
Received Date

Well Name ROGNESS,	Township 143	Range 32	Dir W	Section 33	Subsection DADBDA	Well Depth 74 ft.	Depth Completed 74 ft.	Date Well Completed 11/26/1997
Elevation 1313	Elev. Method LiDAR 1m DEM (MNDNR)						Drill Method Non-specified Rotary	Drill Fluid Bentonite
Address Contact 9515 RISEWOOD CI EDEN PRAIRIE MN 55347						Use domestic	Status Active	
Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND/CLAY 0 15 BROWN SOFT CLAY/BOULDERS 15 23 BROWN MEDIUM SAND 23 30 GRAY SOFT CLAY 30 62 GRAY SOFT SAND 62 74 BLUE SOFT						Well Hydrofractured? Yes ☐ No ☒ From To		
						Casing Type Single casing ☐ Joint ☐		
						Drive Shoe? Yes ☐ No ☐ Above/Below		
						Casing Diameter 4 in. To 64 ft. lbs./ft.		
						Hole Diameter 8 in. To 74 ft.		
						Open Hole From ft. To ft.		
						Screen? ☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 2 in. 15 10 ft. 64 ft. 74 ft.		
						Static Water Level 15 ft. land surface Measure 10/20/1997		
						Pumping Level (below land surface) 40 ft. 1 hrs. Pumping at 40 g.p.m.		
						Wellhead Completion Pitless adapter manufacturer BAKER Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)		
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To high solids bentonite 6 Sacks 0 ft. 40 ft.								
Nearest Known Source of Contamination feet Direction Type Well disinfected upon completion? ☒ Yes ☐ No								
Pump ☐ Not Installed Date Installed 10/20/1997 Manufacturer's name SAT-RITE Model Number HP 0.75 Volt 220 Length of drop pipe ft Capacity 40 g.p. Typ Submersible								
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No								
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No								
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-gray Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 368917 Y 5223862 Unique Number Verification Tax Records Input Date 05/04/2000								
Angled Drill Hole								
Well Contractor Lambert Well Co. 18434 LAMBERT, V. Licensee Business Lic. or Reg. No. Name of Driller								

Remarks