

602926

County Meeker
Quad Rosendale
Quad ID 125C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 12/22/1999
Update Date 03/10/2014
Received Date

Well Name ANDERSON,					Township 119	Range 32	Dir W	Section 26	Subsection BADDBA	Well Depth 269 ft.					Depth Completed 269 ft.					Date Well Completed 06/08/1999									
Elevation 1171					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary					Drill Fluid Bentonite														
Address										Use domestic					Status Active														
Well 23782 549TH GROVE CITY MN 56243										Well Hydrofractured? Yes ☐ No ☒					From To														
Contact 465 BLUFF ST N HUTCHINSON MN 55350										Casing Type Single casing					Joint														
Stratigraphy Information										Drive Shoe? Yes ☐ No ☐					Above/Below														
Geological Material					From	To (ft.)	Color	Hardness		Casing Diameter					Weight	Hole Diameter													
TOPSOIL					0	2	BLACK	SOFT		4 in. To 265 ft. 2 lbs./ft.						8 in. To 21 ft.													
CLAY					2	11	BROWN	SOFT								6.7 in. To 269 ft.													
CLAY					11	21	GRAY	HARD																					
SANDY CLAY					21	96	GRAY	SOFT																					
SAND					96	98	GRAY	SOFT																					
CLAY					98	175	GRAY	HARD																					
SANDY CLAY MIX					175	233	VARIED	SOFT																					
CLAY					233	254	GRAY	SOFT																					
SAND					254	269	GRAY	SOFT																					
										Open Hole					From	ft.	To	ft.											
										Screen? ☒					Type stainless					Make WESCO									
										Diameter					Slot/Gauze					Length					Set				
										4 in.					12					4 ft.					265 ft. 269 ft.				
										Static Water Level					22 ft.					land surface					Measure 06/08/1999				
										Pumping Level (below land surface)					120 ft.					2 hrs.					Pumping at 12 g.p.m.				
										Wellhead Completion					Pitless adapter manufacturer					Model									
										☒ Casing Protection					☒ 12 in. above grade														
										☐ At-grade (Environmental Wells and Borings ONLY)																			
										Grouting Information					Well Grouted? ☒ Yes ☐ No ☐ Not Specified														
										Material					Amount					From					To				
										high solids bentonite					4 Sacks					0 ft. 40 ft.									
										cuttings										40 ft. 245 ft.									
										Nearest Known Source of Contamination					75 feet					South Direction					Open dump Type				
										Well disinfected upon completion?					☒ Yes ☐ No														
										Pump ☐ Not Installed					Date Installed					06/04/1999									
										Manufacturer's name					STA-RITE														
										Model Number					J2000P					HP 0.5					Volt 230				
										Length of drop pipe					120 ft					Capacity 10 g.p.					Typ Submersible				
										Abandoned					Does property have any not in use and not sealed well(s)?					☐ Yes ☒ No									
										Variance					Was a variance granted from the MDH for this well?					☐ Yes ☒ No									
										Miscellaneous					First Bedrock					Aquifer					Quat. buried				
										Last Strat					sand-gray					Depth to Bedrock					ft				
										Located by					Minnesota Geological Survey														
										Locate Method					GPS SA Off (averaged) (15 meters)														
										System					UTM - NAD83, Zone 15, Meters					X 368896					Y 4994523				
										Unique Number Verification					Tax Records					Input Date					06/08/2012				
										Angled Drill Hole																			
										Well Contractor					Barrick, Leroy Well					43607					BEASLEY, M.				
										Licensee Business					Lic. or Reg. No.					Name of Driller									
Minnesota Well Index Report										602926										Printed on 10/02/2026 HE-01205-15									