

Entry Date	05/28/1998
Update Date	02/14/2014
Received Date	

Well Name	Township	Range	Dir Section	Subsection	Well Depth	Depth Completed	Date Well Completed
	39	21	W 15	DCDABD	125 ft.	125 ft.	12/12/1997
Elevation	955 ft.	Elev. Method	7.5 minute topographic map (+/- 5 feet)				
Address							
Well	RR 3 BOX 155H PINE CITY MN 55063						
Contact	105 RAILROAD AV MORA MN 55051						
Stratigraphy Information							
Geological Material	From	To (ft.)	Color	Hardness			
CLAY	0	12	BROWN	MEDIUM			
GRAVEL	12	16	DARK	MEDIUM			
CLAY	16	88	BROWN	HARD			
GRAVEL	88	96	BLACK	MEDIUM			
CLAY	96	114	BROWN	MEDIUM			
SAND	114	125	BROWN	SOFT			
Use domestic Status Active							
Well Hydrofractured? Yes ☐ No ☐ From To							
Casing Type Single casing Joint Glued							
Drive Shoe? Yes ☐ No ☒ Above/Below							
Casing Diameter Weight Hole Diameter							
4 in. To 121 ft. 2 lbs./ft. 8 in. To 125 ft.							
Open Hole From ft. To ft.							
Screen? ☒ Type stainless Make WESCO							
Diameter Slot/Gauze Length Set							
4 in. 10 4 ft. 121 ft. 125 ft.							
Static Water Level							
40 ft. land surface Measure 12/12/1997							
Pumping Level (below land surface)							
60 ft. hrs. Pumping at 40 g.p.m.							
Wellhead Completion							
Pitless adapter manufacturer BAKER Model SNAPPY							
☐ Casing Protection ☒ 12 in. above grade							
☐ At-grade (Environmental Wells and Borings ONLY)							
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified							
Material Amount From To							
bentonite 3 Sacks 0 ft. 30 ft.							
Nearest Known Source of Contamination							
50 feet West Direction Septic tank/drain field Type							
Well disinfected upon completion? ☐ Yes ☐ No							
Pump ☐ Not Installed Date Installed 12/12/1997							
Manufacturer's name FLINT & WALLING							
Model Number HP 0.75 Volt 230							
Length of drop pipe 100 ft Capacity 19 g.p. Typ Submersible							
Abandoned							
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No							
Variance							
Was a variance granted from the MDH for this well? ☐ Yes ☐ No							
Miscellaneous							
First Bedrock Aquifer Quat. buried							
Last Strat sand-brown Depth to Bedrock ft							
Located by Minnesota Geological Survey							
Locate Method Digitized - scale 1:24,000 or larger (Digitizing Table)							
System UTM - NAD83, Zone 15, Meters X 504231 Y 5078753							
Unique Number Verification Information from Input Date 09/01/1998							
Angled Drill Hole							
Well Contractor							
Bill's Well 33655 SUTTON, G.							
Licensee Business Lic. or Reg. No. Name of Driller							
Minnesota Well Index Report				605663		Printed on 10/02/2026 HE-01205-15	