Minnesota Unique Well Number

607308

County Todd
Quad Long Prairie
Quad ID 178A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT

Entry Date 02/22/1999
Update Date 02/14/2014
Received Date

Well Name	Township	Range	Dir	Section	Subsection
CLASEMAN,	129	33	W	28	CBCBBA

Elevation 1325 ft. **Elev. Method** 7.5 minute topographic map (+/- 5 feet)

Address

Well 1310 6TH ST SE LONG PRAIRIE MN 56347

Stratigraphy Information

Geological Material	From	To (ft.)	Color	Hardness
TOPSOIL	0	1	BLACK	SOFT
CLAY	1	15	BROWN	MEDIUM
CLAY	15	73	GRAY	MEDIUM
CLAY	73	80	BROWN	MEDIUM
CLAY	80	133	GRAY	MEDIUM
CLAY	133	140	GRAY	HARD
CLAY	140	185	RED	MEDIUM
CLAY	185	210	GRAY	MEDIUM
CLAY	210	254	GRAY	HARD
SAND	254	262	RED	MEDIUM

Remarks

Well Depth 262 ft. **Depth Completed** 262 ft. **Date Well Completed** 11/06/1997

Drill Method Non-specified Rotary **Drill Fluid** Bentonite

Use domestic **Status** Active

Well Hydrofractured? **Yes** ☐ **No** ☐ **From** **To**

Casing Type Single casing **Joint**
Drive Shoe? **Yes** ☐ **No** ☐ **Above/Below**

Casing Diameter	Weight	Hole Diameter
4 in. To 254 ft.	2 lbs./ft.	7.9 in. To 262 ft.

Open Hole From ft. To ft.

Screen? ☒ **Type** stainless **Make** JOHNSON

Diameter	Slot/Gauze	Length	Set Between
4 in.	12	8 ft.	254 ft. 262 ft.

Static Water Level
19 ft. land surface Measure Date 11/06/1997

Pumping Level (below land surface)
250 ft. after 3 hrs. Pumping at 15 g.p.m.

Wellhead Completion
Pitless adapter manufacturer MAASS Model
☐ Casing Protection ☐ 12 in. above grade
☐ At-grade (Environmental Wells and Borings ONLY)

Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified

Material	Amount	From	To
high solids bentonite		0 ft.	30 ft.

Nearest Known Source of Contamination
76 feet North Direction Septic tank/drain field Type
Well disinfected upon completion? ☒ Yes ☐ No

Pump ☐ Not Installed Date Installed 11/24/1997
Manufacturer's name MEYERS
Model Number 3ST72-12 HP 0.75 Volt 230
Length of drop pipe 160 ft Capacity 12 g.p.m. Type Submersible

Abandoned Wells
Does property have any not in use and not sealed well(s)? ☒ Yes ☐ No

Variance
Was a variance granted from the MDH for this well? ☐ Yes ☒ No

Miscellaneous
First Bedrock Aquifer Quat. buried artes.
Last Strat sand-red Depth to Bedrock ft.
Located by Minnesota Geological Survey
Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or better)
System UTM - NAD83, Zone 15, Meters X 356253 Y 5090481
Unique Number Verification Address verification Input Date 11/11/2003

Angled Drill Hole

Well Contractor Certification
Klimek Bros. Well Drilling, Inc. 21699 KLIMEK, D.
Licensee Business Name Lic. or Reg. No. Name of Driller