

612368

County Lac Qui
Quad Haydenville
Quad ID 132D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/09/1999
Update Date 02/08/2018
Received Date

Well Name WOLLSCHLAGE	Township 118	Range 45	Dir W	Section 23	Subsection BAAACC
Elevation 1087	Elev. Method LiDAR 1m DEM (MNDNR)				
Address C/W RR 3 BOX 13 MADISON MN 56256					
Stratigraphy Information					
Geological Material		From	To (ft.)	Color	Hardness
TOP SOIL		0	2	BLACK	SOFT
CLAY		2	14	YELLOW	MEDIUM
CLAY		14	100	GRAY	MEDIUM
SAND		100	132	GRAY	SOFT
Well Depth 132 ft.					
Depth Completed 132 ft.					
Date Well Completed 08/15/1998					
Drill Method Non-specified Rotary					
Drill Fluid Other					
Use domestic					
Status Active					
Well Hydrofractured? Yes ☐ No ☒ From To					
Casing Type Single casing					
Joint					
Drive Shoe? Yes ☐ No ☐ Above/Below					
Casing Diameter 5 in. To 132 ft.					
Weight lbs./ft.					
Hole Diameter 9 in. To 132 ft.					
Open Hole From ft. To ft.					
Screen? ☒ Type plastic Make EVERFLO					
Diameter Slot/Gauze Length Set					
5 in. 18 10 ft. 122 ft. 132 ft.					
Static Water Level					
22 ft. land surface Measure 08/15/1998					
Pumping Level (below land surface)					
25 ft. 24 hrs. Pumping at 15 g.p.m.					
Wellhead Completion					
Pitless adapter manufacturer MERRILL Model 7'					
☐ Casing Protection ☐ 12 in. above grade					
☐ At-grade (Environmental Wells and Borings ONLY)					
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified					
Material Amount From To					
bentonite 7 ft. 47 ft.					
Nearest Known Source of Contamination					
150 feet East Direction Barnyard Type					
Well disinfected upon completion? ☒ Yes ☐ No					
Pump ☐ Not Installed Date Installed 08/15/1998					
Manufacturer's name GRUNDFOS					
Model Number 1505 HP 0.5 Volt 230					
Length of drop pipe 100 ft Capacity 15 g.p. Typ Submersible					
Abandoned					
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No					
Variance					
Was a variance granted from the MDH for this well? ☐ Yes ☒ No					
Miscellaneous					
First Bedrock					
Last Strat sand-gray					
Aquifer Quat. buried					
Depth to Bedrock ft					
Located by Minnesota Geological Survey					
Locate Method GPS SA Off (averaged) (15 meters)					
System UTM - NAD83, Zone 15, Meters X 243196 Y 4990676					
Unique Number Verification Plat Book Input Date 06/02/2017					
Angled Drill Hole					
Well Contractor					
Minnesota Well Drilling 76067 NESVOLD, J.					
Licensee Business Lic. or Reg. No. Name of Driller					