

612372

County Kandiyohi
Quad Solomon
Quad ID 127A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date04/22/1999

Update Date08/09/2016

Received Date

Well Name DITTMAN,	Township 120	Range 36	Dir W	Section 1	Subsection DAADAA	Well Depth 200 ft.	Depth Completed 200 ft.	Date Well Completed 09/21/1998
Elevation 1184	Elev. Method	LiDAR 1m DEM (MNDNR)				Drill Method Non-specified Rotary	Drill Fluid	Other
Address C/W11088 60TH ST NW PENNOCK MN 56279						Use domestic	Status Active	
						Well Hydrofractured? Yes ☐ No ☒	From	To
Stratigraphy Information						Casing Type Single casing	Joint	
						Drive Shoe? Yes ☐ No ☐	Above/Below	
Geological Material						Casing Diameter	Weight	Hole Diameter
						5 in. To	200 ft.	lbs./ft.
TOPSOIL						Open Hole		
						From	ft.	To
CLAY						Screen? ☒	Type plastic	Make EVERFLO
						Diameter 5 in.	Slot/Gauze 18	Length 20 ft.
CLAY						Static Water Level		
						30 ft.	land surface	Measure
SAND						Pumping Level (below land surface)		
						38 ft.	12 hrs.	Pumping at
						Wellhead Completion		
						Pitless adapter manufacturer ☐ Casing Protection ☐ At-grade (Environmental Wells and Borings ONLY)	MERRILL ☐ 12 in. above grade	Model 7' BURY
						Grouting Information		
						Well Grouted? ☒ Yes ☐ No ☐ Not Specified	Material bentonite	Amount 4 Sacks
						Nearest Known Source of Contamination		
						120 feet	North Direction	Septic tank/drain field Type
						Well disinfected upon completion? ☐ Yes ☐ No		
						Pump ☐ Not Installed	Date Installed	09/21/1998
						Manufacturer's name STA - RITE		
						Model Number 01005	HP 0.5	Volt 230
						Length of drop pipe 100 ft		
						Capacity 10 g.p.	Typ Submersible	
Abandoned						Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No		
						Variance		
Remarks						Was a variance granted from the MDH for this well? ☐ Yes ☒ No		
						Miscellaneous		
						First Bedrock		
						Last Strat sand-gray	Aquifer	Quat. buried Depth to Bedrock ft
						Located by Minnesota Geological Survey		
						Locate Method GPS SA Off (averaged) (15 meters)		
						System UTM - NAD83, Zone 15, Meters		
						X 333264	Y 5010805	
						Unique Number Verification		
						Address verification	Input Date	12/02/2015
						Angled Drill Hole		
						Well Contractor		
						Minnesota Well Drilling	76067	NESVOLD, J.
						Licensee Business		
						Lic. or Reg. No.	Name of Driller	