

618791

CountyOtter Tail
QuadLake
Quad ID238B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date04/02/1999
Update Date10/29/2019
Received Date01/12/1999

Well Name PESHEK, JOHN	Township 137	Range 42	Dir W	Section 22	Subsection CCDAAC	Well Depth 306 ft.	Depth Completed 306 ft.	Date Well Completed 11/15/1998			
Elevation 1338.6	Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary	Drill Fluid Bentonite				
Address C/WRR 3 BOX 263 PELICAN RAPIDS MN 56572						Use domestic	Status Active				
						Well Hydrofractured? Yes ☐ No ☐		From To			
Stratigraphy Information Geological MaterialFromTo (ft.)ColorHardness SOIL01BLACKSOFT CLAY220BROWNMEDIUM CLAY, SAND STRIPES21194BLUEMEDIUM CLAY, ROCK195282BLUEMEDIUM SAND283306GRAYSOFT						Casing Type Single casing	Joint				
						Drive Shoe? Yes ☐ No ☒		Above/Below			
						Casing Diameter 4 in. To 297 ft.		Weight 2 lbs./ft.		Hole Diameter 7 in. To 306 ft.	
						Open HoleFromft.Toft.					
						Screen? ☒ Diameter 4 in.		Type stainless Slot/Gauze 10 Length 10 ft.		Make JOHNSON Set 297 ft. 306 ft.	
						Static Water Level 41 ft. land surface Measure 11/15/1998					
						Pumping Level (below land surface) 41 ft. 2 hrs. Pumping at 30 g.p.m.					
						Wellhead Completion Pitless adapter manufacturer MONITOR Model 4B0 ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)					
						Grouting InformationWell Grouted? ☒ Yes ☐ No ☐ Not Specified MaterialAmountFromTo bentonite3 Sacks0 ft. 40 ft.					
						Nearest Known Source of Contamination <u>100</u> feet <u>South</u> Direction <u>Septic tank/drain field</u> Type Well disinfected upon completion? ☐ Yes ☐ No					
Pump ☐ Not Installed Date Installed <u>11/16/1998</u> Manufacturer's name AERMOTOR Model Number <u>T-12-50</u> HP <u>0.5</u> Volt <u>230</u> Length of drop pipe <u>60</u> ft Capacity <u>12</u> g.p. Typ <u>Submersible</u>											
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No											
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No											
Miscellaneous First BedrockAquifer Quat. buried Last Strat sand-grayDepth to Bedrockft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 272158 Y 5171695 Unique Number VerificationTax RecordsInput Date 09/27/2019											
Angled Drill Hole											
Well Contractor Krueger Well Drill03669LINDSAY, JIM Licensee BusinessLic. or Reg. No.Name of Driller											

Minnesota Well Index Report

618791

Printed on 08/13/2026
HE-01205-15

Remarks