

622724

County Benton
Quad Little Rock
Quad ID 156B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 07/08/1999
Update Date 02/14/2014
Received Date

Well Name WEBER, LARRY				Township 37	Range 31	Dir W	Section 22	Subsection ADDDDA	Well Depth 89 ft.				Depth Completed 89 ft.				Date Well Completed 10/19/1998																					
Elevation 1040				Elev. Method 7.5 minute topographic map (+/- 5 feet)		Drill Method Non-specified Rotary								Drill Fluid Bentonite																								
Address Well 510 80TH ST NW RICE MN 56367										Use domestic				Status Active																								
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>FINE SAND</td><td>0</td><td>31</td><td>BROWN</td><td></td></tr><tr><td>CLAY & ROCKS</td><td>31</td><td>44</td><td>BROWN</td><td></td></tr><tr><td>CLAY</td><td>44</td><td>76</td><td>GRAY</td><td></td></tr><tr><td>SAND</td><td>76</td><td>89</td><td>BROWN</td><td></td></tr></table>										Geological Material	From	To (ft.)	Color	Hardness	FINE SAND	0	31	BROWN		CLAY & ROCKS	31	44	BROWN		CLAY	44	76	GRAY		SAND	76	89	BROWN		Well Hydrofractured? Yes ☐ No ☒ From To			
										Geological Material	From	To (ft.)	Color	Hardness																								
										FINE SAND	0	31	BROWN																									
										CLAY & ROCKS	31	44	BROWN																									
										CLAY	44	76	GRAY																									
										SAND	76	89	BROWN																									
										Casing Type Single casing				Joint																								
										Drive Shoe? Yes ☐ No ☒ Above/Below																												
										Casing Diameter 4 in. To 85 ft.				Weight lbs./ft.				Hole Diameter 8 in. To 89 ft.																				
										Open Hole From ft. To ft.																												
Screen? ☒ Type stainless				Make JOHNSON																																		
Diameter 4 in. Slot/Gauze 15 Length 4 ft. Set 85 ft. 89 ft.																																						
Static Water Level 34 ft. land surface Measure 10/19/1998																																						
Pumping Level (below land surface) 89 ft. 1 hrs. Pumping at 40 g.p.m.																																						
Wellhead Completion Pitless adapter manufacturer MAASS Model 4J1 ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																						
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To high solids bentonite 3 Sacks 0 ft. 30 ft.																																						
Nearest Known Source of Contamination feet Direction Type Well disinfected upon completion? ☒ Yes ☐ No																																						
Pump ☐ Not Installed Date Installed 10/26/1998 Manufacturer's name AERMOTOR Model Number A-12-B-50 HP 0.5 Volt 230 Length of drop pipe 60 ft Capacity 12 g.p. Typ Submersible																																						
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																						
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																						
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-brown Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 408480 Y 5059605 Unique Number Verification Tag on well Input Date 01/22/2008																																						
Angled Drill Hole																																						
Well Contractor Traut M.J. Well Co. 71536 PERRY/MIKE Licensee Business Lic. or Reg. No. Name of Driller																																						

Minnesota Well Index Report	622724	Printed on 08/13/2026 HE-01205-15
-----------------------------	--------	--------------------------------------