

626214

County Faribault
Quad Matawan
Quad ID 33C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/21/2001
Update Date 03/03/2017
Received Date

Well Name BRUEGGER,				Township 104	Range 24	Dir W	Section 8	Subsection CBCCBA	Well Depth 107 ft.	Depth Completed 107 ft.	Date Well Completed 08/25/2000	
Elevation 1097				Elev. Method 7.5 minute topographic map (+/- 5 feet)		Drill Method Driven						Drill Fluid Bentonite
Address C/W 32298 560TH AV WELLS MN 56097												
Stratigraphy Information												
Geological Material				From	To (ft.)	Color	Hardness					
CLAY				0	15	YELLOW						
CLAY				15	101	BLUE						
SAND				101	107	BROWN						
Well Hydrofractured? Yes ☐ No ☐ From To												
Casing Type Single casing Joint Threaded												
Drive Shoe? Yes ☒ No ☐ Above/Below												
Casing Diameter				Weight				Hole Diameter				
5 in. To				101 ft. 15 lbs./ft.				8 in. To 101 ft.				
Open Hole From ft. To ft.												
Screen? ☒ Type stainless Make JOHNSON												
Diameter				Slot/Gauze		Length		Set				
4 in.				20		5 ft.		101 ft.		107 ft.		
Static Water Level												
42 ft.				land surface				Measure		08/25/2000		
Pumping Level (below land surface)												
ft.				hrs.		Pumping at		40		g.p.m.		
Wellhead Completion												
Pitless adapter manufacturer				MONITOR				Model				
☐ Casing Protection				☒ 12 in. above grade								
☐ At-grade (Environmental Wells and Borings ONLY)												
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified												
Material				Amount				From		To		
high solids bentonite				3 Sacks				ft. 30		ft.		
Nearest Known Source of Contamination												
60 feet				Southeas Direction				Septic tank/drain field Type				
Well disinfected upon completion? ☒ Yes ☐ No												
Pump ☐ Not Installed Date Installed 08/28/2000												
Manufacturer's name GRUNDFOS												
Model Number				HP		0.5		Volt		220		
Length of drop pipe				60 ft		Capacity		10 g.p.		Typ Submersible		
Abandoned												
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No												
Variance												
Was a variance granted from the MDH for this well? ☒ Yes ☐ No												
Miscellaneous												
First Bedrock				Aquifer				Quat. buried				
Last Strat sand-brown				Depth to Bedrock				ft				
Located by Minnesota Department of Health												
Locate Method GPS SA Off (averaged) (15 meters)												
System				UTM - NAD83, Zone 15, Meters				X 439862		Y 4852529		
Unique Number Verification								Input Date		08/25/2000		
Angled Drill Hole												
Well Contractor												
Baer Well Co.				07251				BAER, R.				
Licensee Business				Lic. or Reg. No.				Name of Driller				