Minnesota Unique Well Number

627750

County Todd
Quad Round
Quad ID 178B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT

Entry Date 08/03/1999
Update Date 02/04/2025
Received Date 04/12/2024

Well Name	Township	Range	Dir	Section	Subsection
RICHTER, RON & 129	33	W		18	DCDADD

Elevation 1308 ft. **Elev. Method** 7.5 minute topographic map (+/- 5 feet)

Address

C/W 24505 233RD AV LONG PRAIRIE MN 56347

Stratigraphy Information

Geological Material	From	To (ft.)	Color	Hardness
TOP SOIL	0	1	BLACK	MEDIUM
SAND GRAVEL	1	10	BROWN	MEDIUM
CLAY	10	20	BROWN	MEDIUM
CLAY	20	41	GRAY	MEDIUM
SAND	41	45	GRAY	MEDIUM

Remarks

Well Depth	Depth Completed	Date Well Completed
45 ft.	45 ft.	04/21/1999

Drill Method Non-specified Rotary **Drill Fluid** Bentonite

Use domestic **Status** Active

Well Hydrofractured? **Yes** ☐ **No** ☐ **From** **To**

Casing Type Single casing **Joint**
Drive Shoe? **Yes** ☐ **No** ☐ **Above/Below**

Casing Diameter		Weight	
5	in. To 41 ft.	3	lbs./ft.

Open Hole From ft. To ft.

Screen? ☒ **Type** stainless **Make** JOHNSON

Diameter	Slot/Gauze	Length		Set Between			
5	in.	10	4	ft.	41	ft.	45 ft.

Static Water Level
20 ft. land surface Measure Date 04/21/1999

Pumping Level (below land surface)
41 ft. after 2 hrs. Pumping at 100 g.p.m.

Wellhead Completion
Pitless adapter manufacturer MAASS Model
☐ Casing Protection ☐ 12 in. above grade
☐ At-grade (Environmental Wells and Borings ONLY)

Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified

Material	Amount	From	To
bentonite		0 ft.	30 ft.

Nearest Known Source of Contamination
130 feet South Direction Body of water Type
Well disinfected upon completion? ☒ Yes ☐ No

Pump ☐ Not Installed Date Installed 05/24/1999
Manufacturer's name MEYERS
Model Number 3ST102-20 HP 1 Volt 230
Length of drop pipe 30 ft Capacity 20 g.p.m. Type Submersible

Abandoned Wells
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No

Variance
Was a variance granted from the MDH for this well? ☐ Yes ☒ No

Miscellaneous
First Bedrock Aquifer Quat. buried artes.
Last Strat sand-gray Depth to Bedrock ft.
Located by Minnesota Geological Survey
Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or better)
System UTM - NAD83, Zone 15, Meters X 354214 Y 5093250
Unique Number Verification Information from Input Date 08/14/2003

Angled Drill Hole

Well Contractor Certification
Klimek Bros. Well Drilling, Inc. 21699 KLIMEK, D.
Licensee Business Name Lic. or Reg. No. Name of Driller