

Minnesota Unique Well Number

628604

County

Benton

Quad

Quad ID

MINNESOTA DEPARTMENT OF HEALTH

WELL AND BORING REPORT

Minnesota Statutes Chapter 1031

Entry Date

06/30/1999

Update Date

02/14/2014

Received Date

Well Name MOULZOLF,	Township 37	Range 30	Dir Section W 27	Subsection AAA	Well Depth 121 ft.	Depth Completed 121 ft.	Date Well Completed 05/04/1999															
Elevation	Elev. Method					Drill Method Mud Rotary	Drill Fluid Bentonite															
Address Contact9725 HAVLET RD NW RICE MN 56367					Use domestic	Status Active																
					Well Hydrofractured?	Yes ☐	No ☐	From	To													
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY, ROCKS</td><td>0</td><td>113</td><td></td><td></td></tr><tr><td>SAND- FINE</td><td>113</td><td>121</td><td></td><td>MEDIUM</td></tr></table>					Geological Material	From	To (ft.)	Color	Hardness	CLAY, ROCKS	0	113			SAND- FINE	113	121		MEDIUM	Casing Type Single casing	Joint Threaded	
					Geological Material	From	To (ft.)	Color	Hardness													
					CLAY, ROCKS	0	113															
					SAND- FINE	113	121		MEDIUM													
					Drive Shoe?	Yes ☐	No ☒	Above/Below														
					Casing Diameter	Weight		Hole Diameter														
					4 in. To	113 ft.	lbs./ft.	6.7 in. To	121 ft.													
					Open Hole					From	ft.	To	ft.									
					Screen? ☒	Type stainless		Make JOHNSON														
					Diameter	Slot/Gauze	Length	Set														
2 in.	12	8 ft.	113 ft.	121 ft.																		
Static Water Level					30 ft.	land surface	Measure05/04/1999															
Pumping Level (below land surface)					ft.	hrs.	Pumping at12 g.p.m.															
Wellhead Completion					Pitless adapter manufacturerModel																	
☐ Casing Protection					☒ 12 in. above grade																	
☐ At-grade (Environmental Wells and Borings ONLY)																						
Grouting Information					Well Grouted? ☒	Yes ☐	No ☐	Not Specified ☐														
Material					Amount	From	To															
high solids bentonite						0 ft.	30 ft.															
Nearest Known Source of Contamination					feet	Direction	Type															
Well disinfected upon completion?					☒	Yes	☐	No														
Pump ☒					Not Installed	Date Installed																
Manufacturer's name																						
Model Number					HP	Volt																
Length of drop pipe					ft	Capacity	g.p.	Typ														
Abandoned					Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																	
Variance					Was a variance granted from the MDH for this well? ☐ Yes ☒ No																	
Miscellaneous																						
First Bedrock					Aquifer																	
Last Strat					Depth to Bedrock																	
Located by					ft																	
Locate Method																						
System					UTM - NAD83, Zone 15, Meters		X	Y														
Unique Number Verification					Input Date																	
Angled Drill Hole																						
Well Contractor																						
Boart Longyear Drilling					49588		HAMM, RANDY															
Licensee Business					Lic. or Reg. No.		Name of Driller															

Remarks

CASING WEIGHT: 200 PSI

Minnesota Well Index Report

628604

Printed on 10/02/2026
HE-01205-15