

629182

County Wright
Quad French
Quad ID 123B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/06/2000
Update Date 03/18/2011
Received Date

Well Name ORTQUIST,				Township 120	Range 28	Dir W	Section 11	Subsection CCACBD	Well Depth 97 ft.	Depth Completed 97 ft.	Date Well Completed 07/07/1999						
Elevation 1022				Elev. Method 7.5 minute topographic map (+/- 5 feet)		Drill Method Non-specified Rotary						Drill Fluid Other					
Address Well 4156 NORTON AV NW ANNANDALE MN 55302									Use domestic			Status Active					
Stratigraphy Information									Well Hydrofractured? Yes ☐ No ☒				From To				
Geological Material									Casing Type Single casing				Joint Glued				
CLAY									Drive Shoe? Yes ☐ No ☒				Above/Below				
CLAY									Casing Diameter 4 in. To 93 ft.				Weight lbs./ft.	Hole Diameter 6.7 in. To 97 ft.			
SAND									Open Hole From ft. To ft.								
									Screen? ☒				Type stainless	Make JOHNSON			
									Diameter 4 in.				Slot/Gauze 8	Length 4 ft.	Set 93 ft.	97 ft.	
									Static Water Level -15 ft.				land surface		Measure 07/07/1999		
									Pumping Level (below land surface) 5 ft.				1 hrs.		Pumping at 40 g.p.m.		
									Wellhead Completion Pitless adapter manufacturer				WHITEWATER		Model		
									☐ Casing Protection				☐ 12 in. above grade				
									☐ At-grade (Environmental Wells and Borings ONLY)								
									Grouting Information Material				Well Grouted? ☒ Yes ☐ No ☐ Not Specified				
									Amount 13 Sacks				From 6 ft.		To 88 ft.		
									Nearest Known Source of Contamination 51 feet				South		Direction	Septic tank/drain field	Type
									Well disinfected upon completion? ☐ Yes ☐ No								
									Pump ☐ Not Installed				Date Installed 07/15/1999				
									Manufacturer's name AERMOTOR								
									Model Number T12 50				HP 0.5		Volt 230		
									Length of drop pipe 20 ft				Capacity 12 g.p.	Typ Submersible			
									Abandoned Does property have any not in use and not sealed well(s)?				☐ Yes ☒ No				
									Variance Was a variance granted from the MDH for this well?				☐ Yes ☒ No				
									Miscellaneous First Bedrock				Aquifer Quat. buried				
									Last Strat sand				Depth to Bedrock ft				
									Located by Minnesota Geological Survey								
									Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or								
									System UTM - NAD83, Zone 15, Meters				X 407963		Y 5007330		
									Unique Number Verification Tag on well				Input Date 01/27/2010				
									Angled Drill Hole								
									Well Contractor Mattson Well Co.				86108		OESTRIECH, D.		
									Licensee Business				Lic. or Reg. No.		Name of Driller		