

634901

County Crow Wing
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 07/06/2000
Update Date 03/25/2002
Received Date

Well Name ANDERSON,	Township 136	Range 28	Dir W	Section 7	Subsection BAA	Well Depth 129 ft.	Depth Completed 127 ft.	Date Well Completed 10/23/1999
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Bentonite	
Address						Use domestic	Status Active	
Well ROBIN HOOD WA MN						Well Hydrofractured? Yes ☐ No ☒ From To		
Stratigraphy Information						Casing Type Single casing Joint		
Geological Material From To (ft.) Color Hardness						Drive Shoe? Yes ☐ No ☐ Above/Below		
ROCKS, GRAVEL, CLAY 0 6 BROWN						Casing Diameter Weight		
GRAVEL 6 45 YELLOW						4 in. To 115 ft. lbs./ft.		
GRAVEL (MOSTLY 45 128 HARD								
CLAY 128 129								
						Open Hole From ft. To ft.		
						Screen? ☒ Type Make JOHNSON		
						Diameter Slot/Gauze Length Set		
						4 in. 30 12 ft. 115 ft. 127 ft.		
						Static Water Level		
						90 ft. land surface Measure 10/23/1999		
						Pumping Level (below land surface)		
						ft. hrs. Pumping at 9 g.p.m.		
						Wellhead Completion		
						Pitless adapter manufacturer MAASS Model		
						☐ Casing Protection ☒ 12 in. above grade		
						☐ At-grade (Environmental Wells and Borings ONLY)		
						Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
						Material Amount From To		
						high solids bentonite ft. ft.		
						Nearest Known Source of Contamination		
						120 feet East Direction Septic tank/drain field Type		
						Well disinfected upon completion? ☒ Yes ☐ No		
						Pump ☐ Not Installed Date Installed 11/25/1999		
						Manufacturer's name STA-RITE		
						Model Number HP 0.5 Volt 230		
						Length of drop pipe 114 ft Capacity 10 g.p. Typ Submersible		
						Abandoned		
						Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No		
						Variance		
						Was a variance granted from the MDH for this well? ☐ Yes ☒ No		
						Miscellaneous		
						First Bedrock Aquifer		
						Last Strat Depth to Bedrock ft		
						Located by		
						Locate Method		
						System UTM - NAD83, Zone 15, Meters X Y		
						Unique Number Verification Input Date		
						Angled Drill Hole		
						Well Contractor		
						Anderson Well 77201 MARK		
						Licensee Business Lic. or Reg. No. Name of Driller		