

635627

County Stearns
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 06/02/2000
Update Date 03/03/2017
Received Date

Well Name MACKENZIE,	Township 125	Range 34	Dir W	Section 14	Subsection DCC	Well Depth 77 ft.	Depth Completed 77 ft.	Date Well Completed 10/12/1999
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Bentonite	
Address						Use domestic	Status Sealed	
Well 34997 PRESCOTT RD SAUK CENTRE MN 56378						Well Hydrofractured? Yes ☐ No ☐ From To		
Contact 3665 YUMA LA N PLYMOUTH MN 55446						Casing Type Single casing Joint		
Stratigraphy Information						Drive Shoe? Yes ☐ No ☒ Above/Below		
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter Weight Hole Diameter		
CLAY		0	15	YELLOW	MEDIUM	5 in. To 73 ft. lbs./ft. 9 in. To 77 ft.		
CLAY		15	35	BLUE	MEDIUM			
SAND		35	39	BLUE	SOFT			
CLAY		39	71	BLUE	MEDIUM			
SAND		71	77	BLUE	SOFT			
CLAY		77						
Open Hole						From	ft.	To ft.
Screen? ☒						Type stainless	Make JOHNSON	
Diameter		Slot/Gauze	Length	Set				
5 in.		18	4 ft.	73 ft.	77 ft.			
Static Water Level								
18 ft.		land surface		Measure		10/12/1999		
Pumping Level (below land surface)								
70 ft.		1 hrs.	Pumping at		5 g.p.m.			
Wellhead Completion								
Pitless adapter manufacturer						Model		
☐ Casing Protection						☒ 12 in. above grade		
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information						Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
Material		Amount		From	To			
high solids bentonite				0 ft.	30 ft.			
cuttings				30 ft.	70 ft.			
Nearest Known Source of Contamination								
150 feet		Direction				Type		
Well disinfected upon completion?						☒ Yes ☐ No		
Pump ☒ Not Installed						Date Installed		
Manufacturer's name								
Model Number		HP		Volt				
Length of drop pipe		ft	Capacity	g.p.	Typ			
Abandoned								
Does property have any not in use and not sealed well(s)?						☒ Yes ☐ No		
Variance								
Was a variance granted from the MDH for this well?						☐ Yes ☒ No		
Miscellaneous								
First Bedrock		Aquifer						
Last Strat		Depth to Bedrock		ft				
Located by								
Locate Method								
System		UTM - NAD83, Zone 15, Meters		X	Y			
Unique Number Verification						Input Date		
Angled Drill Hole								
Well Contractor								
Atkinson Well Co.		73025		ATKINSON, R.				
Licensee Business		Lic. or Reg. No.		Name of Driller				
Remarks								
SEALED 08-15-2006 BY 2114.								
Minnesota Well Index Report						635627		
						Printed on 08/13/2026 HE-01205-15		