

641303

County Sherburne
Quad Lake
Quad ID 137A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 03/17/2000
Update Date 03/03/2017
Received Date

Well Name 34 Township 26 Range W 22 Dir Section BBCBAD Subsection					Well Depth 58 ft.		Depth Completed 58 ft.		Date Well Completed 11/09/1999	
Elevation 961 ft. Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary		Drill Fluid Bentonite			
Address Well 25189 169 HY ZIMMERMAN MN 55398					Use domestic		Status Sealed			
Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND 0 21 CLAY 21 51 GRAY MEDIUM SAND 51 53 GRAY CLAY, ROCKS 53 58					Well Hydrofractured? Yes ☐ No ☒		From		To	
					Casing Type Single casing		Joint Threaded			
					Drive Shoe? Yes ☐ No ☒		Above/Below			
					Casing Diameter 4 in. To 48 ft.		Weight lbs./ft.		Hole Diameter 6.7 in. To 58 ft.	
					Open Hole From ft. To ft.					
					Screen? ☒		Type plastic		Make JOHNSON	
					Diameter Slot/Gauze Length Set					
					4 in. 16 10 ft. 48 ft. 58 ft.					
					Static Water Level					
					2 ft. land surface		Measure		11/09/1999	
Pumping Level (below land surface)					ft. hrs. Pumping at		5 g.p.m.			
Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)										
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified					Material Amount From To		high solids bentonite 0 ft. 30 ft.			
Nearest Known Source of Contamination					feet Direction				Type	
Well disinfected upon completion? ☒ Yes ☐ No										
Pump ☒ Not Installed Date Installed					Manufacturer's name					
Model Number HP Volt					Length of drop pipe ft Capacity g.p. Typ					
Abandoned					Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No					
Variance					Was a variance granted from the MDH for this well? ☐ Yes ☒ No					
Miscellaneous					First Bedrock Aquifer Quat. buried					
Last Strat pebbly sand/silt/clay					Depth to Bedrock		ft			
Located by Minnesota Geological Survey										
Locate Method GPS SA Off (averaged) (15 meters)										
System UTM - NAD83, Zone 15, Meters X 455304 Y 5030563										
Unique Number Verification Address verification Input Date 11/12/2010										
Angled Drill Hole										
Well Contractor					Boart Longyear Drilling 49588 ANDERSON, J					
Licensee Business					Lic. or Reg. No.		Name of Driller			
Remarks SEALED 10-08-2014 BY 1544.										
Minnesota Well Index Report					641303				Printed on 10/02/2026 HE-01205-15	