

643182

County Hennepin
Quad Rogers
Quad ID 121A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 10/13/2000
Update Date 02/16/2015
Received Date 06/09/2000

Well Name JENDRO,	Township 120	Range 23	Dir Section W 21	Subsection CABCBA	Well Depth 93 ft.	Depth Completed 93 ft.	Date Well Completed 04/12/2000
Elevation 953 ft.	Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary	Drill Fluid Water
Address C/W 25120 HASSAN PK ROGERS MN 55374					Use domestic	Status Active	
Stratigraphy Information Geological Material From To (ft.) Color Hardness CLAY-GRAVEL 0 30 YELLOW SOFT SAND-GRAVEL 30 93 TAN SOFT					Well Hydrofractured? Yes ☐ No ☐ From To		
					Casing Type Single casing Joint		
					Drive Shoe? Yes ☐ No ☐ Above/Below		
					Casing Diameter Weight Hole Diameter		
					4 in. To 87 ft. lbs./ft. 8 in. To 30 ft.		
					6.2 in. To 93 ft.		
					Open Hole From ft. To ft.		
					Screen? ☒ Type stainless Make JOHNSON		
					Diameter Slot/Gauze Length Set		
					2 in. 18 4 ft. 89 ft. 93 ft.		
Static Water Level 70 ft. land surface Measure 04/12/2000							
Pumping Level (below land surface) ft. hrs. Pumping at 18 g.p.m.							
Wellhead Completion Pitless adapter manufacturer WHITEWATER Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)							
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To high solids bentonite 2.5 Sacks 0 ft. 30 ft.							
Nearest Known Source of Contamination <u>100</u> feet <u>Northwes</u> Direction <u>Septic tank/drain field</u> Type Well disinfected upon completion? ☒ Yes ☐ No							
Pump ☐ Not Installed Date Installed <u>04/13/2000</u> Manufacturer's name GOULDS Model Number HP <u>0.75</u> Volt <u>230</u> Length of drop pipe <u>74</u> ft Capacity <u>10</u> g.p. Typ <u>Submersible</u>							
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No							
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No							
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand +larger-brown Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 452998 Y 5003971 Unique Number Verification Address verification Input Date 11/17/2014							
Angled Drill Hole							
Well Contractor Stodola Don Well Co. 27172 LEIBY, F. Licensee Business Lic. or Reg. No. Name of Driller							

Remarks