

645566

County Lake of The
Quad Roosevelt
Quad ID 441A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date01/11/2001

Update Date04/05/2021

Received Date

Well Name MACIOCH,	Township 163	Range 34	Dir W	Section 8	Subsection BCBDBC	Well Depth 45 ft.	Depth Completed 38 ft.	Date Well Completed 10/17/2000
Elevation 1063	Elev. Method LiDAR 1m DEM (MNDNR)	Drill Method Non-specified Rotary		Drill Fluid Bentonite				
Address C/W 6643 TOWNSITE RD NW ROOSEVELT MN 56673						Use domestic		Status Active
Stratigraphy Information						Well Hydrofractured? Yes ☐ No ☐ From To		
Geological Material						Casing Type Single casing Joint		
FINE SAND						Drive Shoe? Yes ☐ No ☒ Above/Below		
CLAY						Casing Diameter		
CLAY						Weight		
FINE SAND						Hole Diameter		
CLAY						4 in. To 38 ft. lbs./ft. 8.5 in. To 20 ft.		
						6.2 in. To 45 ft.		
Open Hole						From ft. To ft.		
Screen? ☒						Type stainless Make		
Diameter Slot/Gauze Length Set						Diameter Length Set		
4 in. 10 8 ft. 30 ft. 38 ft.								
Static Water Level								
5 ft. land surface Measure 10/17/2000								
Pumping Level (below land surface)								
ft. hrs. Pumping at 20 g.p.m.								
Wellhead Completion								
Pitless adapter manufacturer Model								
☐ Casing Protection ☐ 12 in. above grade								
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information						Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
Material Amount From To								
high solids bentonite 30 Sacks 0 ft. 0 ft.								
pearock ft. ft.								
Nearest Known Source of Contamination								
70 feet East Direction Septic tank/drain field Type								
Well disinfected upon completion? ☒ Yes ☐ No								
Pump ☐ Not Installed Date Installed								
Manufacturer's name								
Model Number HP Volt								
Length of drop pipe ft Capacity g.p. Typ								
Abandoned								
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No								
Variance								
Was a variance granted from the MDH for this well? ☐ Yes ☐ No								
Miscellaneous								
First Bedrock Aquifer Quat. buried								
Last Strat clay-gray Depth to Bedrock ft								
Located by Minnesota Geological Survey								
Locate Method GPS SA Off (averaged) (15 meters)								
System UTM - NAD83, Zone 15, Meters X 348582 Y 5424422								
Unique Number Verification Address verification Input Date 04/08/2020								
Angled Drill Hole								
Well Contractor								
Wyland Well Drilling 68729 WYLAND, W								
Licensee Business Lic. or Reg. No. Name of Driller								