Minnesota Unique Well Number

652786

County Todd
Quad Round
Quad ID 178B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT

Entry Date 07/11/2001
Update Date 03/11/2005
Received Date

Well Name	Township	Range	Dir	Section	Subsection
PAUL, TARRANT	129	33	W	18	ACBACB

Elevation 1408 ft. **Elev. Method** 7.5 minute topographic map (+/- 5 feet)

Address

C/W 23177 86 CR LONG PRAIRIE MN 56438

Stratigraphy Information

Geological Material	From	To (ft.)	Color	Hardness
TOP SOIL	0	3	BLACK	MEDIUM
CLAY	3	10	BROWN	MEDIUM
CLAY	10	95	GRAY	MEDIUM
SAND	95	106	GRAY	MEDIUM

Remarks

THIS WELL IS ABOUT 1100 FEET TO NW.

Well Depth 106 ft. **Depth Completed** 106 ft. **Date Well Completed** 10/04/2000

Drill Method Non-specified Rotary **Drill Fluid** Bentonite

Use domestic **Status** Active

Well Hydrofractured? Yes ☐ No ☐ **From** **To**

Casing Type Single casing **Joint**
Drive Shoe? Yes ☐ No ☐ **Above/Below**

Casing Diameter		Weight	
5	in. To 98 ft.	3	lbs./ft.

Open Hole From ft. To ft.

Screen? ☒ **Type** stainless **Make** JOHNSON

Diameter	Slot/Gauze	Length		Set Between			
5	in.	10	8	ft.	98	ft.	106 ft.

Static Water Level

54 ft. land surface Measure Date 10/04/2000

Pumping Level (below land surface)

98 ft. after 2 hrs. Pumping at 100 g.p.m.

Wellhead Completion

Pitless adapter manufacturer MAASS Model

☐ Casing Protection ☐ 12 in. above grade
☐ At-grade (Environmental Wells and Borings ONLY)

Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified

Material	Amount	From	To
high solids bentonite		0 ft.	30 ft.

Nearest Known Source of Contamination

1100 feet South Direction Septic tank/drain field Type

Well disinfected upon completion? ☒ Yes ☐ No

Pump ☐ Not Installed Date Installed 10/07/2000

Manufacturer's name MEYERS

Model Number 3ST102-20 HP 1 Volt 230

Length of drop pipe ft Capacity 20 g.p.m. Type Submersible

Abandoned Wells

Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No

Variance

Was a variance granted from the MDH for this well? ☐ Yes ☒ No

Miscellaneous

First Bedrock Aquifer Quat. buried artes.
Last Strat sand-gray Depth to Bedrock ft.
Located by Minnesota Geological Survey
Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or better)
System UTM - NAD83, Zone 15, Meters X 353973 Y 5094274
Unique Number Verification Information from Input Date 08/14/2003

Angled Drill Hole

Well Contractor Certification

Klimek Bros. Well Drilling, Inc. 21699 KLIMEK, D.
Licensee Business Name Lic. or Reg. No. Name of Driller