

654325

County Washington
Quad Forest Lake
Quad ID 134C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date08/07/2006
Update Date10/13/2011
Received Date10/25/2006

Well Name WALLACE,	Township 32	Range 21	Dir W	Section 17	Subsection CDABCC	Well Depth 70 ft.	Depth Completed 70 ft.	Date Well Completed 06/02/2006
Elevation 897 ft.	Elev. Method 7.5 minute topographic map (+/- 5 feet)	Drill Method Cable Tool						Drill Fluid Bentonite
Address Well21190 FONDANT AV N FOREST LAKE MN 55025						Use domestic	Status Active	
Stratigraphy Information						Well Hydrofractured? Yes ☐ No ☒ From To		
Geological Material						Casing Type Single casing		
From						Joint Welded		
To (ft.)						Drive Shoe? Yes ☒ No ☐ Above/Below		
Color						Casing Diameter		
Hardness						Weight		
SAND CLAY						4 in. To 66 ft. 11 lbs./ft.		
CLAY						8 in. To 15 ft.		
SAND						4 in. To 70 ft.		
						Open Hole Fromft. Toft.		
						Screen? ☒ Type stainless Make JOHNSON		
						Diameter Slot/Gauze Length Set		
						2 in. 12 4 ft. 66 ft. 70 ft.		
						Static Water Level		
						2 ft. land surface Measure 06/02/2006		
						Pumping Level (below land surface)		
						40 ft. 2 hrs. Pumping at 40 g.p.m.		
						Wellhead Completion		
						Pitless adapter manufacturer WHITEWATER Model SU4		
						☐ Casing Protection ☒ 12 in. above grade		
						☐ At-grade (Environmental Wells and Borings ONLY)		
						Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
						Material AmountFromTo		
						bentonite2 Sacksft. ft.		
						Nearest Known Source of Contamination		
						43 feet South Direction Sewer Type		
						Well disinfected upon completion? ☒ Yes ☐ No		
						Pump ☐ Not Installed Date Installed		
						Manufacturer's name WEBTROL		
						Model Number HP 0.5 Volt 220		
						Length of drop pipe 20 ft Capacity 10 g.p. Typ Submersible		
						Abandoned		
						Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No		
						Variance		
						Was a variance granted from the MDH for this well? ☒ Yes ☐ No		
						Miscellaneous		
						First Bedrock Aquifer Quat. buried		
						Last Strat sand-brown Depth to Bedrock ft		
						Located by Minnesota Geological Survey		
						Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or		
						System UTM - NAD83, Zone 15, Meters X 500691 Y 5011461		
						Unique Number Verification Info/GPS from data Input Date 05/02/2006		
						Angled Drill Hole		
						Well Contractor		
						Miggler Well Drilling 1453 MIGGLER, L.		
						Licensee Business Lic. or Reg. No. Name of Driller		