

669407

County Pine
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 02/01/2002
Update Date 03/11/2005
Received Date

Well Name R.G. HUDLOW					Township 38	Range 21	Dir W	Section 9	Subsection DAD	Well Depth 350 ft.		Depth Completed 350 ft.		Date Well Completed 12/14/2001			
Elevation					Elev. Method					Drill Method Non-specified Rotary		Drill Fluid Qwik gel					
Address										Use domestic		Status Active					
Contact RR 3 BOX 95F PINE CITY MN 55063										Well Hydrofractured? Yes ☐ No ☐ From To							
Stratigraphy Information										Casing Type Single casing		Joint Welded					
Geological Material										Drive Shoe? Yes ☒ No ☐		Above/Below					
CLAY										Casing Diameter 4 in. To		Weight 118 ft. lbs./ft.		Hole Diameter 6 in. To 118 ft.			
CLAY																	
CLAY																	
CLAY GRAVEL																	
CLAY GRAVEL ROCKS																	
CLAY GRAVEL																	
CLAY																	
SANDSTONE																	
										Open Hole From 118 ft. To 350 ft.							
										Screen? ☐		Type		Make			
Static Water Level										50 ft. land surface		Measure		12/14/2001			
Pumping Level (below land surface)										100 ft. 2 hrs. Pumping at		10 g.p.m.					
Wellhead Completion										Pitless adapter manufacturer		SNAPPY		Model			
										☐ Casing Protection		☐ 12 in. above grade					
										☐ At-grade (Environmental Wells and Borings ONLY)							
Grouting Information										Well Grouted? ☒ Yes ☐ No ☐ Not Specified							
Material										Amount		From		To			
high solids bentonite										2 Sacks		5 ft.		30 ft.			
Nearest Known Source of Contamination										55 feet		Northwes Direction		<u>Septic tank/drain field</u> Type			
										Well disinfected upon completion?		☒ Yes ☐ No					
Pump ☐ Not Installed										Date Installed		12/14/2001					
Manufacturer's name										STA RITE							
Model Number										HP 0.75		Volt 230					
Length of drop pipe										100 ft		Capacity 10 g.p.		Typ Submersible			
Abandoned										Does property have any not in use and not sealed well(s)?		☐ Yes ☒ No					
Variance										Was a variance granted from the MDH for this well?		☐ Yes ☒ No					
Miscellaneous										First Bedrock		Aquifer					
										Last Strat		Depth to Bedrock		ft			
Located by										Locate Method							
System										UTM - NAD83, Zone 15, Meters		X		Y			
Unique Number Verification												Input Date					
Angled Drill Hole																	
Well Contractor										Sampson Well Co.		82673		BELISLE, K.			
										Licensee Business		Lic. or Reg. No.		Name of Driller			