

672386

County Anoka
Quad Anoka
Quad ID 120B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 12/30/2002
Update Date 07/29/2008
Received Date

Well Name KLABOUGH,					Township 32	Range 25	Dir W	Section 30	Subsection ACAADD	Well Depth 70 ft.				Depth Completed 70 ft.				Date Well Completed 05/20/2002					
Elevation 849 ft.					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary				Drill Fluid Bentonite									
Address Well 14660 BOWERS DR NW RAMSEY MN 55303										Use domestic										Status Active			
Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND 0 8 BROWN SOFT GRAVEL, ROCKS 8 52 BROWN SOFT CLAY 52 54 BROWN MEDIUM GRAVEL, ROCKS 54 70 BROWN SOFT CLAY 70 70 GRAY MEDIUM										Well Hydrofractured? Yes ☐ No ☒ From To													
										Casing Type Single casing Joint													
										Drive Shoe? Yes ☐ No ☒ Above/Below													
										Casing Diameter 4 in. To 65 ft. 1.9 lbs./ft.										Hole Diameter 6.5 in. To 70 ft.			
										Open Hole From ft. To ft.													
										Screen? ☒ Type stainless Make JOHNSON													
										Diameter Slot/Gauze Length Set													
										2 in. 12 5 ft. 65 ft. 70 ft.													
										Static Water Level 14 ft. land surface Measure 05/20/2002													
										Pumping Level (below land surface) 65 ft. 2 hrs. Pumping at 30 g.p.m.													
Wellhead Completion Pitless adapter manufacturer MONITOR Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																							
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To high solids bentonite 0.17 Cubic yards 0 ft. 30 ft. cuttings 30 ft. 65 ft.																							
Nearest Known Source of Contamination 40 feet East Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No																							
Pump ☐ Not Installed Date Installed 09/04/2002 Manufacturer's name AERMOTOR Model Number T12-75 HP 0.75 Volt 230 Length of drop pipe 40 ft Capacity 15 g.p. Typ Submersible																							
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																							
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																							
Miscellaneous First Bedrock Aquifer Quat. Water Last Strat clay-gray Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 461066 Y 5009376 Unique Number Verification Address verification Input Date 07/03/2008																							
Angled Drill Hole																							
Well Contractor Mc Alpine Brothers 27636 MCALPINE, B. Licensee Business Lic. or Reg. No. Name of Driller																							

Minnesota Well Index Report	672386	Printed on 10/02/2026 HE-01205-15
-----------------------------	--------	--------------------------------------