

693683

County Itasca
Quad La Prairie
Quad ID 272B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 08/04/2004
Update Date 01/17/2025
Received Date 02/03/2004

Well Name STOLTZ,					Township 54	Range 24	Dir W	Section 8	Subsection ADADCD	Well Depth 131 ft.			Depth Completed 131 ft.			Date Well Completed 05/21/2003		
Elevation 1276					Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary			Drill Fluid Bentonite					
Address										Use domestic			Status Active					
Well 20871 BLUEBIRD DR GRAND RAPIDS MN										Well Hydrofractured? Yes ☐ No ☒			From To					
Contact 25899 DOVE LA GRAND RAPIDS MN 55744										Casing Type Single casing			Joint					
Stratigraphy Information										Drive Shoe? Yes ☐ No ☒			Above/Below					
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter			Weight			Hole Diameter						
TOP SOIL		0	1	BLACK	SOFT	4 in. To			123 ft. 2.25 lbs./ft.			6.7 in. To 131 ft.						
CLAY SAND		1	15	BROWN	SOFT													
CLAY SAND		15	26	BLUE	SOFT													
CLAY		26	38	BLUE	SOFT													
CLAY		38	45	RED	MEDIUM													
CLAY		45	115	BLUE	SOFT													
SILT		115	120	BLUE	SOFT													
SAND		120	131	BLUE	SOFT													
Open Hole										From		ft.		To		ft.		
Screen?		☒		Type		stainless		Make		JOHNSON								
Diameter		Slot/Gauze		Length		Set		Make		JOHNSON								
4 in.		7		8 ft.		123 ft.		131 ft.										
Static Water Level										28 ft.		land surface		Measure		05/21/2003		
Pumping Level (below land surface)										120 ft.		1 hrs.		Pumping at		20 g.p.m.		
Wellhead Completion										Pitless adapter manufacturer		MONITOR		Model		SNAPPY		
☐		Casing Protection		☐		12 in. above grade												
☐		At-grade (Environmental Wells and Borings ONLY)																
Grouting Information										Well Grouted?		☒ Yes ☐ No ☐ Not Specified						
Material		Amount		From		To												
high solids bentonite		3 Sacks		ft. 30		ft.												
Nearest Known Source of Contamination										feet		Direction		Type				
Well disinfected upon completion?										☒ Yes ☐ No								
Pump										☐ Not Installed		Date Installed		06/03/2003				
Manufacturer's name										GOULDS								
Model Number		10SB05-422		HP		0.5		Volt		230								
Length of drop pipe		60 ft		Capacity		10 g.p.		Typ		Submersible								
Abandoned										Does property have any not in use and not sealed well(s)?		☐ Yes ☒ No						
Variance										Was a variance granted from the MDH for this well?		☐ Yes ☒ No						
Miscellaneous										First Bedrock		Aquifer						
Last Strat		Depth to Bedrock		ft														
Located by		Minnesota Geological Survey																
Locate Method		Digitization (Screen) - Map (1:24,000) (15 meters or																
System		UTM - NAD83, Zone 15, Meters		X 469136		Y 5224809												
Unique Number Verification		Address verification		Input Date		01/09/2025												
Angled Drill Hole																		
Well Contractor										Benes Well Co.		31009		GOODELL, M				
Licensee Business		Lic. or Reg. No.		Name of Driller														
Minnesota Well Index Report					693683					Printed on 10/02/2026 HE-01205-15								