

695229

County Itasca
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 08/10/2004
Update Date 03/20/2026
Received Date 02/03/2004

Well Name NELSON, LARRY 58					Township 25					Range W 10					Dir Section CAC					Subsection					Well Depth 63 ft.					Depth Completed 63 ft.					Date Well Completed 06/21/2003				
Elevation					Elev. Method					Drill Method Non-specified Rotary					Drill Fluid Bentonite					Use domestic					Status Active														
Address																																							
Contact					413 BUFFALO RUN RD BUFFALO MN 55313																																		
Well					44362 WILDVIEW LA BOVEY MN 55709																																		
Stratigraphy Information																																							
Geological Material					From					To (ft.)					Color					Hardness																			
TOP SOIL					0					3					BLACK					SOFT																			
SAND					3					50					BROWN					SOFT																			
FINE SAND					50					59					BLUE					SOFT																			
AQUIFER					59					63					BLUE					SOFT																			
Open Hole																																							
Screen?					From					ft.					To					ft.																			
☒																																							
Type					stainless					Make					JOHNSON																								
Diameter					Slot/Gauze					Length					Set																								
4 in.					10					4 ft.					59 ft.					63 ft.																			
Static Water Level																																							
24 ft.					land surface					Measure					06/21/2003																								
Pumping Level (below land surface)																																							
50 ft.					2 hrs.					Pumping at					6 g.p.m.																								
Wellhead Completion																																							
Pitless adapter manufacturer					MONITOR					Model					SNAPPY																								
☐ Casing Protection					☐ 12 in. above grade																																		
☐ At-grade (Environmental Wells and Borings ONLY)																																							
Grouting Information																																							
Well Grouted?					☒ Yes					☐ No					☐ Not Specified																								
Material					Amount					From					To																								
high solids bentonite					3 Sacks					ft. 30					ft.																								
Nearest Known Source of Contamination																																							
50 feet					West Direction					Septic tank/drain field					Type																								
Well disinfected upon completion?					☒ Yes					☐ No																													
Pump																																							
☐ Not Installed					Date Installed					06/23/2003																													
Manufacturer's name					GOULDS																																		
Model Number					10SB05-422					HP					0.5					Volt					230														
Length of drop pipe					47 ft					Capacity					10 g.p.					Typ					Submersible														
Abandoned																																							
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																							
Variance																																							
Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																							
Miscellaneous																																							
First Bedrock					Aquifer																																		
Last Strat					Depth to Bedrock										ft																								
Located by																																							
Locate Method																																							
System					UTM - NAD83, Zone 15, Meters					X					Y																								
Unique Number Verification										Input Date																													
Angled Drill Hole																																							
Well Contractor																																							
Benes Well Co.					31009					BENES, E																													
Licensee Business					Lic. or Reg. No.					Name of Driller																													
Minnesota Well Index Report										695229					Printed on 08/13/2026 HE-01205-15																								