

716308

County Beltrami
Quad Bemidji
Quad ID 302A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/13/2006
Update Date 09/04/2025
Received Date 12/09/2005

Well Name DOBSON,	Township 146	Range 32	Dir W	Section 8	Subsection DADDCA	Well Depth 124 ft.	Depth Completed 124 ft.	Date Well Completed 04/01/2005			
Elevation 1355	Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary	Drill Fluid Bentonite				
Address C/W 931 FROHN RD NE BEMIDJI MN 56601						Use domestic	Status Active				
Stratigraphy Information						Well Hydrofractured?	Yes ☐	No ☒	From	To	
						Casing Type Single casing	Joint				
						Drive Shoe?	Yes ☐	No ☒	Above/Below		
Geological Material						Casing Diameter	Weight	Hole Diameter			
CLAY						4 in. To	120 ft. 0 lbs./ft.	6.7 in. To 124 ft.			
SANDY CLAY											
CLAY											
SAND											
						Open Hole	From	ft.	To	ft.	
						Screen? ☒	Type	stainless	Make	JOHNSON	
						Diameter	Slot/Gauze	Length	Set		
						2 in.	10	4 ft.	120 ft.	124 ft.	
						Static Water Level					
						15 ft.	land surface	Measure	04/01/2005		
						Pumping Level (below land surface)					
						22 ft.	1 hrs.	Pumping at	40	g.p.m.	
						Wellhead Completion					
						Pitless adapter manufacturer			Model		
						☐	Casing Protection		☒	12 in. above grade	
						☐	At-grade (Environmental Wells and Borings ONLY)				
						Grouting Information					
						Well Grouted? ☒ Yes ☐ No ☐ Not Specified					
						Material	Amount	From	To		
						high solids bentonite	2 Sacks	8 ft.	30 ft.		
						Nearest Known Source of Contamination					
						70 feet	Southeas Direction		Septic tank/drain field Type		
						Well disinfected upon completion? ☒ Yes ☐ No					
						Pump ☒	Not Installed		Date Installed		
						Manufacturer's name					
						Model Number	HP	Volt			
						Length of drop pipe	ft	Capacity	g.p.	Typ	
						Abandoned					
						Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No					
						Variance					
						Was a variance granted from the MDH for this well? ☐ Yes ☒ No					
						Miscellaneous					
						First Bedrock	Aquifer		Quat. buried		
						Last Strat	sand-gray	Depth to Bedrock		ft	
						Located by Minnesota Geological Survey					
						Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or					
						System	UTM - NAD83, Zone 15, Meters	X 367612	Y 5259198		
						Unique Number Verification	Tax Records	Input Date	04/23/2025		
						Angled Drill Hole					
						Well Contractor					
						Aqua Well Drilling	04463	WILSON, J.			
						Licensee Business	Lic. or Reg. No.	Name of Driller			