

722218

County Sherburne
Quad Becker
Quad ID 138A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 04/16/2011
Received Date 08/08/2005

Well Name 34 28 W 36 AAAADA					Well Depth 88 ft.		Depth Completed 88 ft.		Date Well Completed 06/16/2005			
Elevation 976 ft. Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary		Drill Fluid Bentonite					
Address Well 19434 118TH ST BECKER MN 55308					Use domestic		Status Active					
Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND 0 10 BROWN SOFT CLAY 10 20 TAN SOFT CLAY & GRAVEL 20 73 TAN SOFT SAND 73 88 BROWN SOFT					Well Hydrofractured? Yes ☐ No ☒		From		To			
					Casing Type Single casing		Joint Glued					
					Drive Shoe? Yes ☐ No ☒		Above/Below					
					Casing Diameter		Weight		Hole Diameter			
					4 in. To 80 ft. 0 lbs./ft.				8.5 in. To 30 ft. 6.5 in. To 88 ft.			
					Open Hole		From ft. To ft.					
					Screen? ☒		Type stainless		Make JOHNSON			
					Diameter Slot/Gauze Length Set							
					2 in. 25 8 ft. 80 ft. 88 ft.							
					Static Water Level 50 ft. land surface Measure 06/16/2005							
Pumping Level (below land surface) ft. 1 hrs. Pumping at 30 g.p.m.												
Wellhead Completion Pitless adapter manufacturer MONITOR Model SNAPPY ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)												
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified												
Material Amount From To												
high solids bentonite 3 Sacks 0 ft. 30 ft.												
cuttings 0 30 ft. 80 ft.												
Nearest Known Source of Contamination 63 feet Northeas Direction Other Type												
Well disinfected upon completion? ☒ Yes ☐ No												
Pump ☐ Not Installed Date Installed 07/29/2005												
Manufacturer's name RED JACKET												
Model Number 75F211/12G HP 0.75 Volt 230												
Length of drop pipe 60 ft Capacity 15 g.p. Typ Submersible												
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No												
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No												
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-brown Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 440701 Y 5027664 Unique Number Verification Address verification Input Date 03/01/2011												
Angled Drill Hole												
Well Contractor Mork Well Co., Inc. 02730 DEE, M. Licensee Business Lic. or Reg. No. Name of Driller												
Remarks												