

726568

County Martin
Quad Truman SE
Quad ID 36D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 06/14/2006
Update Date 10/13/2023
Received Date 04/20/2006

Well Name SALIC, MIKE					Township 103	Range 29	Dir W	Section 4	Subsection BCBCDB	Well Depth 95 ft.				Depth Completed 95 ft.				Date Well Completed 03/26/2006					
Elevation 1111					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary				Drill Fluid Bentonite									
Address Well 1868 270TH AV GRANADA MN 56039										Use domestic										Status Active			
Stratigraphy Information Geological Material From To (ft.) Color Hardness TOP SOIL 0 3 BLACK SOFT CLAY 3 18 YELLOW SOFT CLAY 18 75 BLUE SOFT SAND 75 95 GRAY SOFT										Well Hydrofractured? Yes ☐ No ☒ From To													
										Casing Type Single casing Joint													
										Drive Shoe? Yes ☐ No ☒ Above/Below													
										Casing Diameter 5 in. To 90 ft. 0 lbs./ft.										Hole Diameter 9 in. To 95 ft.			
										Open Hole From ft. To ft.													
										Screen? ☒ Type stainless Make JOHNSON													
										Diameter Slot/Gauze Length Set													
										5 in. 20 5 ft. 90 ft. 95 ft.													
										Static Water Level 22 ft. land surface Measure 03/26/2006													
										Pumping Level (below land surface) 40 ft. 2 hrs. Pumping at 20 g.p.m.													
Wellhead Completion Pitless adapter manufacturer MAAS Model 5X1.25 ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																							
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To high solids bentonite 6 Sacks ft. 89 ft.																							
Nearest Known Source of Contamination 25 feet <u>Northeas</u> Direction Well disinfected upon completion? ☒ Yes ☐ No <u>Old/other well</u> Type																							
Pump ☐ Not Installed Date Installed <u>03/27/2006</u> Manufacturer's name GRUNDFOS Model Number <u>10SQE0524</u> HP <u>0.5</u> Volt <u>230</u> Length of drop pipe <u>40</u> ft Capacity <u>10</u> g.p. Typ <u>Submersible</u>																							
Abandoned Does property have any not in use and not sealed well(s)? ☒ Yes ☐ No																							
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																							
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-gray Depth to Bedrock ft Located by Minnesota Department of Health Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 393182 Y 4845558 Unique Number Verification Input Date 05/02/2006																							
Angled Drill Hole																							
Well Contractor Beemer Well Drilling, Inc. 1494 KOLLASCH, T. Licensee Business Lic. or Reg. No. Name of Driller																							
Remarks																							