

735869

County Anoka
Quad Centerville
Quad ID 119A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/09/2007
Update Date 03/25/2010
Received Date 09/18/2006

Well Name BOASCH, RAY				Township 32	Range 22	Dir W	Section 35	Subsection CBAABB
Elevation 901 ft.		Elev. Method 7.5 minute topographic map (+/- 5 feet)						
Address Well 8341 136TH AV NE FOREST LAKE MN 55025								
Stratigraphy Information								
Geological Material		From	To (ft.)	Color	Hardness			
SAND		0	20	BROWN				
CLAY		20	60	GRAY				
SAND & GRAVEL		60	84					
Well Depth 84 ft.		Depth Completed 84 ft.		Date Well Completed 08/03/2006				
Drill Method Non-specified Rotary		Drill Fluid Bentonite						
Use domestic		Status Active						
Well Hydrofractured?		Yes ☐	No ☒	From		To		
Casing Type Single casing		Joint						
Drive Shoe?		Yes ☐	No ☒	Above/Below				
Casing Diameter 4 in.		Weight 80 ft.		Hole Diameter 8 in.		84 ft.		
Open Hole		From	ft.	To	ft.			
Screen? ☒		Type stainless		Make JOHNSON				
Diameter		Slot/Gauze	Length	Set				
in.		15	4 ft.	80 ft.	84 ft.			
Static Water Level								
14 ft.		land surface		Measure		08/03/2006		
Pumping Level (below land surface)								
84 ft.		1 hrs.		Pumping at		50 g.p.m.		
Wellhead Completion								
Pitless adapter manufacturer		SNAPPY		Model		1"		
☐ Casing Protection		☒ 12 in. above grade						
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information		Well Grouted?		☒ Yes	☐ No	☐ Not Specified		
Material		Amount		From		To		
high solids bentonite		3 Sacks		ft.		30 ft.		
Nearest Known Source of Contamination								
70 feet		Northwes		Direction		Sewer Type		
Well disinfected upon completion?		☒ Yes		☐ No				
Pump		☐ Not Installed		Date Installed		08/07/2006		
Manufacturer's name		GRUNDFOES						
Model Number		SQE		HP		1		Volt
Length of drop pipe		60 ft		Capacity		g.p.		Typ
Submersible								
Abandoned								
Does property have any not in use and not sealed well(s)?		☐ Yes		☒ No				
Variance								
Was a variance granted from the MDH for this well?		☐ Yes		☒ No				
Miscellaneous								
First Bedrock		Aquifer		Quat. buried				
Last Strat		sand +larger		Depth to Bedrock		ft		
Located by		Minnesota Geological Survey						
Locate Method		GPS SA Off (averaged) (15 meters)						
System		UTM - NAD83, Zone 15, Meters		X		495579		Y 5007146
Unique Number Verification		Address verification		Input Date		02/08/2010		
Angled Drill Hole								
Well Contractor								
Barott Drilling Services, Inc.		1860		BAROTT				
Licensee Business		Lic. or Reg. No.		Name of Driller				
Minnesota Well Index Report				735869		Printed on 08/13/2026 HE-01205-15		