

745512

County Kanabec
Quad Mora North
Quad ID 172A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 07/25/2007
Update Date 04/28/2015
Received Date 07/23/2007

Well Name EVENSON,					Township 40	Range 24	Dir W	Section 35	Subsection CBDABA	Well Depth 65 ft.		Depth Completed 65 ft.		Date Well Completed 05/29/2007									
Elevation 996 ft.					Elev. Method 7.5 minute topographic map (+/- 5 feet)		Drill Method Non-specified Rotary								Drill Fluid Bentonite								
Address Well 2028 226TH AV MORA MN 55051										Use domestic		Status Active											
Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND 0 2 CLAY GRAVEL 2 35 SANDSTONE 35 65										Well Hydrofractured? Yes ☐ No ☒						From		To					
										Casing Type Single casing						Joint Threaded							
										Drive Shoe? Yes ☒ No ☐						Above/Below							
										Casing Diameter 4 in. To 42 ft.						Weight lbs./ft.				Hole Diameter 8 in. To 42 ft. 4 in. To 65 ft.			
										Open Hole From 42 ft. To 65 ft.													
										Screen? ☐						Type				Make			
										Static Water Level 12 ft. land surface Measure 05/29/2007													
										Pumping Level (below land surface) 60 ft. 2 hrs. Pumping at 25 g.p.m.													
										Wellhead Completion Pitless adapter manufacturer SNAPPY Model SNAPPY ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)													
										Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 3 Sacks 0 ft. 40 ft.													
Nearest Known Source of Contamination 50 feet East Direction Septic tank/drain field Type Well disinfected upon completion? ☐ Yes ☐ No																							
Pump ☐ Not Installed Date Installed 06/05/2007 Manufacturer's name GOULDS Model Number HP 1 Volt 230 Length of drop pipe 36 ft Capacity 20 g.p. Typ Submersible																							
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																							
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																							
Miscellaneous First Bedrock Fond du Lac Formation Aquifer Fond Du Lac Last Strat Fond du Lac Formation Depth to Bedrock 35 ft Located by Minnesota Department of Health Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 476499 Y 5084074 Unique Number Verification Input Date 05/29/2007																							
Angled Drill Hole																							
Well Contractor Mora Well Co. 1512 KELLER, W. Licensee Business Lic. or Reg. No. Name of Driller																							
Remarks																							