

751714

County Le Sueur
Quad Le Sueur
Quad ID 74B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/08/2008
Update Date 07/24/2025
Received Date 09/06/2007

Well Name LINDEMAR, LISA 111					Township 26		Range W 12		Dir Section DDAAAB		Well Depth 178 ft.		Depth Completed 178 ft.		Date Well Completed 08/15/2007				
Elevation 891 ft.					Elev. Method LiDAR 1m DEM (MNDNR)							Drill Method Non-specified Rotary		Drill Fluid Bentonite					
Address												Use domestic		Status Active					
Well 35780 311TH AV LE SUEUR MN												Well Hydrofractured? Yes ☒ No ☐				From		To	
Contact 36366 OTTAWA RD LE SUEUR MN 56058												Casing Type Single casing		Joint Threaded					
Stratigraphy Information												Drive Shoe? Yes ☒ No ☐		Above/Below					
Geological Material		From		To (ft.)		Color		Hardness		Casing Diameter		Weight		Hole Diameter					
CLAY SAND		0		12		BROWN				5 in. To 144 ft.		lbs./ft.		9.5 in. To 20 ft.					
GRAVEL SAND		12		55		BROWN								7.8 in. To 144 ft.					
CLAY		55		118		GRAY								4.7 in. To 178 ft.					
GRAVEL CLAY/		118		142		BRN/GRY MEDIUM													
LIMEROCKS		142		178		BROWN HARD													
												Open Hole		From 144 ft.		To 178 ft.			
												Screen? ☐		Type		Make			
Static Water Level												130 ft.		land surface		Measure		08/15/2007	
Pumping Level (below land surface)												ft.		hrs.		Pumping at		20 g.p.m.	
Wellhead Completion												Pitless adapter manufacturer		MONITOR		Model			
												☐ Casing Protection		☐ 12 in. above grade					
												☐ At-grade (Environmental Wells and Borings ONLY)							
Grouting Information												Well Grouted? ☒ Yes ☐ No ☐ Not Specified							
Material		Amount		From		To													
bentonite		2 Sacks		10		ft. 50		ft.											
Nearest Known Source of Contamination												38 feet		Southwes Direction		Livestock watering Type			
Well disinfected upon completion?												☐ Yes ☐ No							
Pump ☐ Not Installed												Date Installed		09/05/2007					
Manufacturer's name												FLINT & WALLING							
Model Number		HP		0.75		Volt		220											
Length of drop pipe		147		ft		Capacity		10		g.p.		Typ		Submersible					
Abandoned												Does property have any not in use and not sealed well(s)?		☐ Yes ☒ No					
Variance												Was a variance granted from the MDH for this well?		☐ Yes ☒ No					
Miscellaneous												First Bedrock		Aquifer					
Last Strat				Depth to Bedrock		142		ft											
Located by		Minnesota Geological Survey																	
Locate Method		Digitization (Screen) - Map (1:24,000) (15 meters or																	
System		UTM - NAD83, Zone 15, Meters		X 429197		Y 4920182													
Unique Number Verification		Tag on well		Input Date		08/27/2024													
Angled Drill Hole																			
Well Contractor												Bohn Well Drilling Co., Inc.		1445		VON BANK, B			
Licensee Business				Lic. or Reg. No.		Name of Driller													