

752437

County Nicollet
Quad St George
Quad ID 77A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 03/10/2010
Received Date 05/09/2008

Well Name SCHWAB, PAT					Township 111	Range 31	Dir W	Section 9	Subsection CBCCDA	Well Depth 235 ft.	Depth Completed 235 ft.	Date Well Completed 11/09/2007		
Elevation 1013					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary	Drill Fluid Bentonite			
Address										Use domestic	Status Active			
Well 35799 651ST AV GIBBON MN										Well Hydrofractured? Yes ☐ No ☒ From To				
Contact 14287 ESPRIT DR WESTFIELD IN 46074										Casing Type Single casing Joint Welded				
Stratigraphy Information										Drive Shoe? Yes ☐ No ☒ Above/Below				
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter Weight Hole Diameter								
SOIL		0	2	BLACK	SOFT	6 in. To 225 ft. lbs./ft. 9 in. To 235 ft.								
CLAY SANDY		2	18	YELLOW	SOFT									
CLAY SANDY		18	72	BLUE	SOFT									
VERY COARSE SAND		72	85	VARIED	SOFT									
CLAY SANDY (FIRM)		85	127	GRAY										
CLAY VERY SANDY		127	142	GRAY	SOFT									
FINE MEDIUM SAND		142	154	BROWN										
CLAY VERY SANDY		154	197	GRAY	M.HARD									
MEDIUM SAND (FIRM)		197	235	BROWN										
Open Hole										From	ft.	To	ft.	
Screen? ☒										Type stainless		Make JOHNSON		
Diameter		Slot/Gauze		Length		Set								
6 in.		18		13 ft.		225 ft.		235 ft.						
Static Water Level														
206 ft.		land surface				Measure		11/09/2007						
Pumping Level (below land surface)														
ft.		hrs.		Pumping at		10		g.p.m.						
Wellhead Completion														
Pitless adapter manufacturer										Model				
☐ Casing Protection										☐ 12 in. above grade				
☐ At-grade (Environmental Wells and Borings ONLY)														
Grouting Information										Well Grouted? ☒ Yes ☐ No ☐ Not Specified				
Material		Amount		From		To								
cuttings				60 ft.		ft.								
bentonite		5 Sacks		ft. 60		ft.								
Nearest Known Source of Contamination														
220 feet		South		Direction		Old/other well		Type						
Well disinfected upon completion?										☒ Yes ☐ No				
Pump ☒ Not Installed										Date Installed				
Manufacturer's name														
Model Number		HP		Volt										
Length of drop pipe		ft		Capacity		g.p.		Typ						
Abandoned														
Does property have any not in use and not sealed well(s)?										☐ Yes ☒ No				
Variance														
Was a variance granted from the MDH for this well?										☐ Yes ☒ No				
Miscellaneous														
First Bedrock		Aquifer		Quat. buried										
Last Strat		sand-brown		Depth to Bedrock		ft								
Located by Minnesota Geological Survey														
Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or														
System		UTM - NAD83, Zone 15, Meters		X 374868		Y 4920952								
Unique Number Verification		Address verification		Input Date		03/16/2009								
Angled Drill Hole														
Well Contractor														
Searles Well Drilling, Inc.		1493		KUCK, R.										
Licensee Business		Lic. or Reg. No.		Name of Driller										
Minnesota Well Index Report					752437					Printed on 08/13/2026 HE-01205-15				