

753638		County Goodhue	MINNESOTA DEPARTMENT OF HEALTH				Entry Date 10/28/2014			
		Quad Welch	WELL AND BORING REPORT				Update Date 06/14/2018			
		Quad ID 86C	Minnesota Statutes Chapter 1031				Received Date 12/15/2014			
Well Name LEXVOID, TONY		Township 112	Range 16	Dir W	Section 13	Subsection BDBBAA	Well Depth 480 ft.	Depth Completed 480 ft.	Date Well Completed 11/15/2014	
Elevation 1082		Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary	Drill Fluid Foam		
Address							Use domestic	Status Active		
C/W 30240 19 HY RED WING MN 55066							Well Hydrofractured? Yes ☐ No ☒ From To			
Stratigraphy Information							Casing Type Step down		Joint Welded	
							Drive Shoe? Yes ☒ No ☐		Above/Below	
Geological Material		From	To (ft.)	Color	Hardness		Casing Diameter		Weight	Hole Diameter
CLAY-GRAVEL		0	34	BROWN	SOFT		4 in. To 462 ft.		10.79 lbs./ft.	12 in. To 40 ft.
LIMEROCK P.D.C		34	305	TAN/BRN	HARD		8 in. To 40 ft.		lbs./ft.	8 in. To 480 ft.
SANDROCK JORDAN		305	404	YEL/GRY	SOFT					
SANDROCK ST.		404	452	GRAY	HARD					
SANDROCK		452	480	GRN/BRN	MEDIUM					
Open Hole							From 462 ft.	To 480 ft.		
Screen? ☐							Type		Make	
Static Water Level										
197 ft.							land surface	Measure	11/05/2014	
Pumping Level (below land surface)										
260 ft.							12 hrs.	Pumping at	10 g.p.m.	
Wellhead Completion										
Pitless adapter manufacturer MAASS							Model			
☐ Casing Protection							☒ 12 in. above grade			
☐ At-grade (Environmental Wells and Borings ONLY)										
Grouting Information							Well Grouted? ☒ Yes ☐ No ☐ Not Specified			
Material							Amount	From	To	
neat cement							12.5 Sacks	ft.	462 ft.	
Nearest Known Source of Contamination										
feet							Direction		Type	
Well disinfected upon completion?							☐ Yes	☐ No		
Pump ☐ Not Installed							Date Installed 11/14/2014			
Manufacturer's name SCHAEFER										
Model Number 10LD15S43							HP 1.5	Volt 220		
Length of drop pipe 21 ft							Capacity 12 g.p.	Typ Submersible		
Abandoned										
Does property have any not in use and not sealed well(s)?							☐ Yes	☒ No		
Variance										
Was a variance granted from the MDH for this well?							☐ Yes	☒ No		
Miscellaneous										
First Bedrock Prairie Du Chien Group							Aquifer	Tunnel City		
Last Strat Tunnel City Group							Depth to Bedrock 34	ft		
Located by Minnesota Geological Survey										
Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or										
System UTM - NAD83, Zone 15, Meters							X 525007	Y 4928640		
Unique Number Verification							Information from	Input Date 10/28/2014		
Angled Drill Hole										
Well Contractor										
Terry Maher Well Drilling,							1908	KAASE, B.		
Licensee Business							Lic. or Reg. No.	Name of Driller		
Minnesota Well Index Report			753638		Printed on 10/02/2026 HE-01205-15					