

756018

County Itasca
Quad Bovey
Quad ID 296C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 05/21/2026
Received Date 11/10/2007

Well Name CAMPBELL,	Township 57	Range 24	Dir W	Section 34	Subsection CCDAAB	Well Depth 168 ft.	Depth Completed 166 ft.	Date Well Completed 11/10/2007
Elevation 1362	Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary	Drill Fluid Bentonite	
Address						Use domestic	Status Active	
Well 34122 SCENIC HY BOVEY MN 55709						Well Hydrofractured? Yes ☐ No ☒ From To		
Contact 34077 SCENIC HY BOVEY MN 55709						Casing Type Single casing Joint Glued		
Stratigraphy Information						Drive Shoe? Yes ☐ No ☒ Above/Below		
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter Weight Hole Diameter		
CLAY ROCK		0	34	BROWN	HARD	4 in. To 158 ft. lbs./ft. 8 in. To 166 ft.		
CLAY ROCK		34	163	GRAY	HARD			
SAND		163	168	GRAY	SOFT			
Open Hole						From	ft.	To ft.
Screen? ☒						Type stainless	Make JOHNSON	
Diameter		Slot/Gauze	Length	Set				
2 in.		10	8 ft.	158 ft.	166 ft.			
Static Water Level								
34 ft.		land surface		Measure		11/10/2007		
Pumping Level (below land surface)								
134 ft.		4 hrs.	Pumping at		0.25 g.p.m.			
Wellhead Completion								
Pitless adapter manufacturer		BAKER		Model		BULLDOG		
☐ Casing Protection		☒ 12 in. above grade						
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information						Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
Material		Amount		From		To		
bentonite		3 Sacks		ft.		30 ft.		
Nearest Known Source of Contamination								
51 feet		North Direction		Septic tank/drain field		Type		
Well disinfected upon completion?						☒ Yes ☐ No		
Pump ☐ Not Installed						Date Installed	11/10/2007	
Manufacturer's name						RED JACKET		
Model Number		HP		0.5		Volt	115	
Length of drop pipe		126 ft		Capacity	10 g.p.		Typ	
Abandoned								
Does property have any not in use and not sealed well(s)?						☐ Yes ☒ No		
Variance								
Was a variance granted from the MDH for this well?						☐ Yes ☒ No		
Miscellaneous								
First Bedrock		sand-gray		Aquifer		Quat. buried		
Last Strat		sand-gray		Depth to Bedrock		ft		
Located by						Minnesota Geological Survey		
Locate Method						Digitization (Screen) - Map (1:24,000) (15 meters or		
System		UTM - NAD83, Zone 15, Meters		X 471192		Y 5246542		
Unique Number Verification		Tax Records		Input Date		01/09/2025		
Angled Drill Hole								
Well Contractor								
B and R Bowman Wells And		1682		BOWMAN, B				
Licensee Business		Lic. or Reg. No.		Name of Driller				