

760966

County Faribault
Quad Winnebago
Quad ID 35C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 11/26/2012
Update Date 09/29/2020
Received Date 01/27/2011

Well Name SCHNEIDER,	Township 104	Range 28	Dir W	Section 20	Subsection DDDDDC	Well Depth 150 ft.	Depth Completed 150 ft.	Date Well Completed 12/02/2010
Elevation 1082	Elev. Method	LiDAR 1m DEM (MNDNR)				Drill Method Non-specified Rotary	Drill Fluid Water	
Address C/W 32969 210TH ST WINNEBAGO MN 56098						Use domestic	Status Active	
Stratigraphy Information Geological Material From To (ft.) Color Hardness TOPSOIL 0 2 BLACK SOFT CLAY 2 25 BROWN MEDIUM CLAY 25 85 BLUE MEDIUM SAND 85 90 BROWN SOFT CLAY 90 130 BLUE HARD SANDSTONE 130 150 BROWN HARD						Well Hydrofractured? Yes ☐ No ☒ From To		
						Casing Type Single casing Joint		
						Drive Shoe? Yes ☐ No ☐ Above/Below		
						Casing Diameter Weight Hole Diameter 5 in. To 145 ft. lbs./ft. 10 in. To 150 ft.		
						Open Hole From ft. To ft.		
						Screen? ☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 4 in. 12 5 ft. 145 ft. 150 ft.		
						Static Water Level 40 ft. land surface Measure 12/02/2010		
						Pumping Level (below land surface) 80 ft. 3 hrs. Pumping at 20 g.p.m.		
						Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)		
						Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To well grouted, type unknown 8 Sacks 0 ft. 130 ft.		
Nearest Known Source of Contamination 125 feet North Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No								
Pump ☒ Not Installed Date Installed Manufacturer's name Model Number HP Volt Length of drop pipe ft Capacity g.p. Typ								
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No								
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No								
Miscellaneous First Bedrock Cretaceous undiff. Aquifer Cretaceous, Last Strat Cretaceous undiff. Depth to Bedrock 130 ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 402792 Y 4849198 Unique Number Verification Address verification Input Date 03/26/2020								
Angled Drill Hole								
Well Contractor Jerrys Well Service, Inc. 1462 ULRICH, J. Licensee Business Lic. or Reg. No. Name of Driller								