

763779

County Benton
Quad Ronneby
Quad ID 155A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 09/23/2008
Update Date 10/17/2013
Received Date 08/19/2008

Well Name EVENSON					Township 37	Range 28	Dir W	Section 26	Subsection AACBCD	Well Depth 65 ft.				Depth Completed 56 ft.				Date Well Completed 06/24/2008																															
Elevation 1101					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary				Drill Fluid Bentonite																																			
Address Well 18252 75TH ST FOLEY MN 56329										Use domestic										Status Active																													
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>10</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>SAND</td><td>10</td><td>14</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY & ROCKS</td><td>14</td><td>38</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>SAND & GRAVEL</td><td>38</td><td>58</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>58</td><td>65</td><td>BROWN</td><td>MEDIUM</td></tr></table>										Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	10	BROWN	MEDIUM	SAND	10	14	BROWN	SOFT	CLAY & ROCKS	14	38	BROWN	MEDIUM	SAND & GRAVEL	38	58	BROWN	SOFT	CLAY	58	65	BROWN	MEDIUM	Well Hydrofractured? Yes ☐ No ☒ From To									
										Geological Material	From	To (ft.)	Color	Hardness																																			
										CLAY	0	10	BROWN	MEDIUM																																			
										SAND	10	14	BROWN	SOFT																																			
										CLAY & ROCKS	14	38	BROWN	MEDIUM																																			
										SAND & GRAVEL	38	58	BROWN	SOFT																																			
										CLAY	58	65	BROWN	MEDIUM																																			
										Casing Type Single casing										Joint																													
										Drive Shoe? Yes ☐ No ☒ Above/Below																																							
										Casing Diameter 4 in. To 52 ft.				Weight 2.94 lbs./ft.				Hole Diameter 8 in. To 65 ft.																															
Open Hole From ft. To ft.																																																	
Screen? ☒ Type stainless										Make JOHNSON																																							
Diameter 4 in.				Slot/Gauze 18				Length 4 ft.				Set 52 ft. 56 ft.																																					
Static Water Level 5 ft. null										Measure 06/24/2008																																							
Pumping Level (below land surface) 56 ft. 1 hrs. Pumping at 35 g.p.m.																																																	
Wellhead Completion Pitless adapter manufacturer MASSS Model 4J1 ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																																	
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																																																	
Material bentonite				Amount 7 Sacks				From ft. 40 ft.																																									
Nearest Known Source of Contamination feet Direction Type																																																	
Well disinfected upon completion? ☒ Yes ☐ No																																																	
Pump ☐ Not Installed Date Installed 07/11/2008																																																	
Manufacturer's name SCHAEFER																																																	
Model Number 16P10				HP 1				Volt 230																																									
Length of drop pipe 40 ft				Capacity 16 g.p.				Typ Submersible																																									
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																																	
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																																	
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat clay-brown Depth to Bedrock ft Located by Minnesota Department of Health Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 438766 Y 5058201 Unique Number Verification Input Date 07/22/2008																																																	
Angled Drill Hole																																																	
Well Contractor Mark J Traut Wells, Inc. 1404 ROBBIE/RYAN Licensee Business Lic. or Reg. No. Name of Driller																																																	

Minnesota Well Index Report	763779	Printed on 08/13/2026 HE-01205-15
-----------------------------	--------	--------------------------------------