

765344

County Anoka
Quad Coon Lake
Quad ID 135C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/08/2009
Update Date 05/27/2014
Received Date 01/13/2009

Well Name MINKS CUSTOM	Township 32	Range 23	Dir W	Section 11	Subsection BDCAAC	Well Depth 145 ft.	Depth Completed 145 ft.	Date Well Completed 11/19/2008
Elevation 908 ft.	Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary	Drill Fluid Bentonite	
Address Well 3658 169TH LA NE HAM LAKE MN 55304						Use domestic	Status Active	
Stratigraphy Information						Well Hydrofractured? Yes ☐ No ☒	From To	
Geological Material						Casing Type Single casing	Joint Above/Below	
SAND						Drive Shoe? Yes ☐ No ☒	Drive Shoe? Yes ☐ No ☒	
CLAY & GRAVEL						Casing Diameter 4 in.	Weight 135 ft.	Hole Diameter 6.7 in.
CLAY & GRAVEL								
SAND & GRAVEL								
						Open Hole From ft. To ft.		
						Screen? ☒	Type plastic	Make BIG FOOT
						Diameter 4 in.	Slot/Gauze 15	Length 10 ft.
							Set 135 ft.	ft. 145 ft.
						Static Water Level 15 ft.	land surface	Measure 11/19/2008
						Pumping Level (below land surface) 60 ft.	3 hrs.	Pumping at 25 g.p.m.
						Wellhead Completion Pitless adapter manufacturer	MAASS	Model
						☐ Casing Protection	☒ 12 in. above grade	
						☐ At-grade (Environmental Wells and Borings ONLY)		
						Grouting Information Material	Well Grouted? ☒ Yes ☐ No ☐ Not Specified	
						Amount cuttings	From 50 ft.	To 135 ft.
						well grouted, type unknown	5 Sacks	ft. 50 ft.
						Nearest Known Source of Contamination 50 feet	East Direction	Sewer Type
						Well disinfected upon completion? ☒ Yes ☐ No		
						Pump ☐ Not Installed	Date Installed 11/19/2008	
						Manufacturer's name SCHAEFER	HP 0.75	Volt 230
						Length of drop pipe 40 ft	Capacity 12 g.p.	Typ Submersible
						Abandoned Does property have any not in use and not sealed well(s)?	☐ Yes ☒ No	
						Variance Was a variance granted from the MDH for this well?	☐ Yes ☒ No	
						Miscellaneous First Bedrock	Aquifer Quat. buried	
						Last Strat sand +larger-brown	Depth to Bedrock ft	
						Located by Minnesota Geological Survey		
						Locate Method Digitization (Screen) - Map (1:12,000) (>15 meters)		
						System UTM - NAD83, Zone 15, Meters	X 486186	Y 5013827
						Unique Number Verification Address verification	Input Date 03/01/2010	
						Angled Drill Hole		
						Well Contractor A Ruppert Well, Inc.	1572	BASTIAN, W.
						Licensee Business	Lic. or Reg. No.	Name of Driller