

766580

County Swift
Quad Milan NW
Quad ID 130B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date12/29/2008

Update Date11/05/2021

Received Date10/29/2008

Well Name WEST-CON	Township 121	Range 42	Dir W	Section 35	Subsection CDCDBB
Elevation 1032	Elev. Method LiDAR 1m DEM (MNDNR)				
Address Contact101 RAND ST HOLLOWAY MN 56249					
Stratigraphy Information					
Geological Material		From	To (ft.)	Color	Hardness
TOPSOIL		0	6	BLACK	MEDIUM
CLAY		6	19	YELLOW	MEDIUM
CLAY		19	31	BLUE	MEDIUM
CLAY		31	44	BLUE	HARD
GRAVEL		44	56	GRAY	MEDIUM
GRAVEL COARSE		56	67	GRAY	
Well Depth67 ft. Depth Completed67 ft. Date Well Completed09/08/2008					
Drill Method Non-specified Rotary		Drill Fluid Bentonite			
Use commercial				Status Active	
Well Hydrofractured? Yes ☐ No ☒ From To					
Casing Type Joint					
Drive Shoe? Yes ☐ No ☐ Above/Below					
Casing Diameter		Weight		Hole Diameter	
5 in. To		ft. lbs./ft.		9 in. To 67 ft.	
Open Hole From ft. To ft.					
Screen? ☒		Type stainless		Make JOHNSON	
Diameter		Slot/Gauze		Set	
5 in.		60		10 ft. 57 ft. 67 ft.	
Static Water Level					
20 ft.		land surface		Measure 09/08/2008	
Pumping Level (below land surface)					
50 ft.		8 hrs. Pumping at		30 g.p.m.	
Wellhead Completion					
Pitless adapter manufacturer				Model	
☐ Casing Protection		☐ 12 in. above grade			
☐ At-grade (Environmental Wells and Borings ONLY)					
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified					
Material		Amount		From To	
bentonite				ft. 50 ft.	
Nearest Known Source of Contamination					
190 feet		West Direction		Septic tank/drain field Type	
Well disinfected upon completion? ☒ Yes ☐ No					
Pump ☐ Not Installed Date Installed09/30/2008					
Manufacturer's name SCHAFFER					
Model Number		HP2		Volt208	
Length of drop pipe		50 ft		Capacity40 g.p. Typ Submersible	
Abandoned					
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No					
Variance					
Was a variance granted from the MDH for this well? ☐ Yes ☒ No					
Miscellaneous					
First Bedrock		Aquifer		Quat. buried	
Last Strat		gravel (+larger)-gray		Depth to Bedrock ft	
Located by Minnesota Department of Health					
Locate Method GPS SA Off (averaged) (15 meters)					
System		UTM - NAD83, Zone 15, Meters		X 271963 Y 5013738	
Unique Number Verification		Info/GPS from data		Input Date11/05/2008	
Angled Drill Hole					
Well Contractor					
Jacobs, Jacobs and Larson		1902		JACOBS, T.	
Licensee Business		Lic. or Reg. No.		Name of Driller	