

778253

County

Stearns

Quad

Sauk

Quad ID

159B

MINNESOTA DEPARTMENT OF HEALTH

WELL AND BORING REPORT

Minnesota Statutes Chapter 1031

Entry Date

01/24/2011

Update Date

06/08/2011

Received Date

11/08/2010

Well Name ILGEN, DUSTIN Township 126 Range 34 Dir Section W 15 Subsection DAADBC Elevation 1243 Elev. Method Calc from DEM (USGS 7.5 min or equiv.) Address Well39547 415TH ST SAUK CENTRE MN 56378 Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>COARSE GRAVEL</td><td>0</td><td>41</td><td>BROWN</td><td></td></tr><tr><td>CLAY</td><td>41</td><td>82</td><td>BLUE</td><td>SOFT</td></tr><tr><td>VERY FINE SAND</td><td>82</td><td>87</td><td>GRAY</td><td></td></tr></table>	Geological Material	From	To (ft.)	Color	Hardness	COARSE GRAVEL	0	41	BROWN		CLAY	41	82	BLUE	SOFT	VERY FINE SAND	82	87	GRAY		Well Depth 87 ft. Depth Completed 87 ft. Date Well Completed 09/29/2010 Drill Method Non-specified Rotary Drill Fluid Bentonite Use domestic Status Active Well Hydrofractured? Yes☐ No☐ From To Casing Type Joint Drive Shoe? Yes☐ No☐ Above/Below Casing Diameter Weight Hole Diameter 4 in. To 83 ft. lbs./ft.8.5 in. To 22 ft.7.5 in. To 87 ft. Open Hole Fromft. Toft. Screen?☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 4 in.104 ft.83 ft.87 ft. Static Water Level 30 ft. land surface Measure 09/28/2010 Pumping Level (below land surface) 80 ft. 30 hrs. Pumping at 35 g.p.m. Wellhead Completion Pitless adapter manufacturer MERRILL Model SPK ☐ Casing Protection☐ 12 in. above grade☐ At-grade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? ☒ Yes☐ No☐ Not Specified Material bentonite Amount From To ft.50ft. Nearest Known Source of Contamination feet Direction Well disinfected upon completion? ☒ Yes☐ No Type Pump☐ Not Installed Date Installed 11/01/2010 Manufacturer's name GRUNDFOS Model Number HP 1 Volt 240 Length of drop pipe 60 ft Capacity g.p. Typ Submersible Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes☒ No Variance Was a variance granted from the MDH for this well? ☐ Yes☒ No Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Minnesota Department of Health Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 349487 Y 5065002 Unique Number Verification Info/GPS from data Input Date 10/22/2010 Angled Drill Hole Well Contractor Dons Pump and Well Service 1451 MEULEBROEK, D Licensee Business Lic. or Reg. No. Name of Driller
Geological Material	From	To (ft.)	Color	Hardness																	
COARSE GRAVEL	0	41	BROWN																		
CLAY	41	82	BLUE	SOFT																	
VERY FINE SAND	82	87	GRAY																		
Remarks	Minnesota Well Index Report	778253	Printed on 08/13/2026 HE-01205-15																		