

778565

County Olmsted
Quad Zumbro
Quad ID 49B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 10/18/2012
Update Date 01/19/2017
Received Date 03/06/2012

Well Name DAVIS,					Township 108	Range 14	Dir Section W 24	Subsection CAAADA	Well Depth 378 ft.					Depth Completed 378 ft.					Date Well Completed 02/09/2012															
Elevation 1030					Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary					Drill Fluid Foam																			
Address										Use domestic										Status Active														
Well 9937 11TH AV NE ROCHESTER MN 55906										Well Hydrofractured? Yes ☐ No ☒										From To														
Contact 4486 56TH ST NW ROCHESTER MN 55901										Casing Type Single casing										Joint Welded														
Stratigraphy Information										Drive Shoe? Yes ☒ No ☐										Above/Below														
Geological Material					From	To (ft.)	Color	Hardness	Casing Diameter					Weight					Hole Diameter															
DRIFT					0	18			4 in. To 319 ft.					lbs./ft.					12 in. To 20 ft.															
LIMESTONE					18	275													8 in. To 319 ft.															
SANDSTONE					275	378													4 in. To 378 ft.															
										Open Hole										From 319 ft. To 378 ft.														
										Screen? ☐										Type					Make									
										Static Water Level										90 ft. land surface					Measure 02/08/2012									
										Pumping Level (below land surface)										100 ft. 2 hrs. Pumping at					15 g.p.m.									
										Wellhead Completion										Pitless adapter manufacturer MONITOR Model 4X6														
										☐ Casing Protection										☐ 12 in. above grade														
										☐ At-grade (Environmental Wells and Borings ONLY)																								
										Grouting Information										Well Grouted? ☒ Yes ☐ No ☐ Not Specified														
										Material					Amount					From					To									
										pearock					2.5 Cubic yards					20 ft. 275 ft.														
										neat cement					5 Cubic yards					ft. 319 ft.														
										Nearest Known Source of Contamination										50 feet Direction					Type									
										Well disinfected upon completion? ☒ Yes ☐ No																								
										Pump ☐ Not Installed Date Installed 02/09/2012																								
										Manufacturer's name GRUNDFOS																								
										Model Number 15SQE1529					HP 1.5					Volt 230														
										Length of drop pipe 147 ft					Capacity 15 g.p.					Typ Submersible														
										Abandoned										Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No														
										Variance										Was a variance granted from the MDH for this well? ☐ Yes ☒ No														
										Miscellaneous										First Bedrock Prairie Du Chien Group					Aquifer Jordan									
										Last Strat Jordan Sandstone					Depth to Bedrock 18 ft																			
										Located by Minnesota Geological Survey																								
										Locate Method GPS SA Off (averaged) (15 meters)																								
										System UTM - NAD83, Zone 15, Meters					X 544075					Y 4887956														
										Unique Number Verification					Address verification					Input Date 11/05/2015														
										Angled Drill Hole																								
										Well Contractor										Thein Well Rochester, Inc. 2641					KRAUSE, M.									
										Licensee Business					Lic. or Reg. No.					Name of Driller														
Remarks																																		
Minnesota Well Index Report										778565										Printed on 08/13/2026 HE-01205-15														