

Minnesota Unique Well Number

779310

County

Anoka

Quad

Cedar

Quad ID

136D

MINNESOTA DEPARTMENT OF HEALTH

WELL AND BORING REPORT

Minnesota Statutes Chapter 1031

Entry Date

02/02/2011

Update Date

02/14/2014

Received Date

12/15/2010

Well Name PINEWSKI Township 33 Range 24 Dir Section W 12 Subsection DCABDB	Well Depth 100 ft. Depth Completed 100 ft. Date Well Completed 12/03/2010																									
Elevation 923 ft. Elev. Method Calc from DEM (USGS 7.5 min or equiv.)	Drill Method Non-specified Rotary Drill Fluid Bentonite																									
Address Well 21480 EVERGREEN ST OAK GROVE MN 55011	Use domestic Status Active																									
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>GRAVEL</td><td>0</td><td>31</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>31</td><td>36</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>CLAY, GRAVEL, ROCKS</td><td>36</td><td>78</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>GRAVEL</td><td>78</td><td>100</td><td>YELLOW</td><td>SOFT</td></tr></table>	Geological Material	From	To (ft.)	Color	Hardness	GRAVEL	0	31	BROWN	SOFT	CLAY	31	36	GRAY	MEDIUM	CLAY, GRAVEL, ROCKS	36	78	BROWN	MEDIUM	GRAVEL	78	100	YELLOW	SOFT	Well Hydrofractured? Yes ☐ No ☒ From To
	Geological Material	From	To (ft.)	Color	Hardness																					
	GRAVEL	0	31	BROWN	SOFT																					
	CLAY	31	36	GRAY	MEDIUM																					
	CLAY, GRAVEL, ROCKS	36	78	BROWN	MEDIUM																					
	GRAVEL	78	100	YELLOW	SOFT																					
	Casing Type Single casing Joint Glued	Drive Shoe? Yes ☐ No ☒ Above/Below																								
	Casing Diameter 4 in. To 90 ft. Weight lbs./ft. Hole Diameter 8 in. To 50 ft. 6.5 in. To 100 ft.																									
	Open Hole From ft. To ft.																									
	Screen? ☒ Type plastic Make BIGFOOT																									
Diameter 4 in. Slot/Gauze 20 Length 10 ft. Set 90 ft. 100 ft.																										
Static Water Level 26 ft. land surface Measure 12/03/2010																										
Pumping Level (below land surface) 90 ft. 2 hrs. Pumping at 50 g.p.m.																										
Wellhead Completion Pitless adapter manufacturer AQUASEAL Model 1"																										
Casing Protection ☐ 12 in. above grade ☒ At-grade (Environmental Wells and Borings ONLY)																										
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																										
Material bentonite Amount 5 Sacks From 0 ft. To 50 ft. cuttings 50 ft. 90 ft.																										
Nearest Known Source of Contamination 54 feet West Direction Well disinfected upon completion? ☒ Yes ☐ No Sewer Type																										
Pump ☐ Not Installed Date Installed 12/06/2010																										
Manufacturer's name AERMOTOR Model Number AT1250 HP 0.5 Volt 230																										
Length of drop pipe 60 ft. Capacity g.p. Typ Submersible																										
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																										
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																										
Remarks	Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft																									
	Located by Minnesota Department of Health																									
	Locate Method GPS SA Off (averaged) (15 meters)																									
	System UTM - NAD83, Zone 15, Meters X 478659 Y 5022878																									
	Unique Number Verification Info/GPS from data Input Date 12/03/2010																									
	Angled Drill Hole																									
	Well Contractor Mork Well Co., Inc. 1877 GOODIN, G.																									
	Licensee Business Lic. or Reg. No. Name of Driller																									

Minnesota Well Index Report

779310

Printed on 08/13/2026
HE-01205-15