

779923

County Meeker
Quad Hutchinson
Quad ID 108A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date08/21/2012
Update Date10/15/2012
Received Date07/16/2012

Well Name PRIEVE, DAN	Township 118	Range 29	Dir W	Section 32	Subsection DCCBDB	Well Depth 141 ft.	Depth Completed 134 ft.	Date Well Completed 05/23/2012		
Elevation 1087	Elev. Method 7.5 minute topographic map (+/- 5 feet)				Drill Method Non-specified Rotary	Drill Fluid Bentonite				
Address C/W 70586 COMMON ST HUTCHINSON MN 55350						Use domestic	Status Active			
Stratigraphy Information Geological MaterialFromTo (ft.)ColorHardness SAND/GRAVEL04VARIED SANDY CLAY422YELLOW SANDY CLAY2244GRAY SAND4449GRAY SANDY CLAY49124GRAY SAND124141VARIED						Well Hydrofractured? Yes ☐ No ☐ From To				
						Casing Type Single casing			Joint Glued	
						Drive Shoe? Yes ☐ No ☒			Above/Below	
						Casing Diameter 4 in. To 126 ft.			Weight lbs./ft.	
									Hole Diameter 6.7 in. To 141 ft.	
Open Hole Fromft.Toft.										
Screen? ☒ Type stainless Make JOHNSON										
DiameterSlot/GauzeLengthSet										
4 in. 15 8 ft. 126 ft. 134 ft.										
Static Water Level 29 ft. land surface Measure 05/18/2012										
Pumping Level (below land surface) 76 ft. hrs. Pumping at 25 g.p.m.										
Wellhead Completion Pitless adapter manufacturer MONITOR Model 6PS45BS4CO ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)										
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified										
MaterialAmountFromTo										
bentonite 6 Sacks 6 ft. 116 ft.										
Nearest Known Source of Contamination 60 feet South Direction Septic tank/drain field Type										
Well disinfected upon completion? ☒ Yes ☐ No										
Pump ☐ Not Installed Date Installed 05/23/2012										
Manufacturer's name SCHAEFER										
Model Number 10LD05 HP 0.5 Volt 230										
Length of drop pipe 84 ft Capacity 10 g.p. Typ Submersible										
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No										
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No										
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand Depth to Bedrock ft Located by Minnesota Department of Health Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 393788 Y 4981636 Unique Number Verification Info/GPS from data Input Date 06/27/2012										
Angled Drill Hole										
Well Contractor LTP Enterprises, Inc. 2157 GRIMM, G. Licensee Business Lic. or Reg. No. Name of Driller										