

780770

County Otter Tail
Quad Vergas
Quad ID 238A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 10/07/2011
Update Date 07/16/2018
Received Date 06/16/2011

Well Name BEARDSLEY,				Township 137	Range 41	Dir W	Section 35	Subsection DADBDD	Well Depth 80 ft.	Depth Completed 76 ft.	Date Well Completed 03/23/2011																																									
Elevation 1384				Elev. Method LiDAR 1m DEM (MNDNR)		Drill Method Non-specified Rotary						Drill Fluid Qwik gel																																								
Address Contact 28926 KORONIS DR PAYNESVILLE MN 56362 Well 32327 LOON DR VERGAS MN 56587									Use domestic		Status Active																																									
Stratigraphy Information									Well Hydrofractured? Yes ☐ No ☐			From To																																								
<table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>GRAVEL</td><td>0</td><td>20</td><td>BROWN</td><td></td></tr><tr><td>CLAY</td><td>20</td><td>41</td><td>BROWN</td><td></td></tr><tr><td>SAND, LITTLE WATER</td><td>41</td><td>56</td><td></td><td></td></tr><tr><td>SAND, 20 SLOT</td><td>56</td><td>63</td><td></td><td></td></tr><tr><td>SAND, 15 SLOT</td><td>63</td><td>71</td><td>BROWN</td><td></td></tr><tr><td>SAND, 15 SLOT</td><td>71</td><td>76</td><td>GRAY</td><td></td></tr><tr><td>SAND, FINE</td><td>76</td><td>80</td><td></td><td></td></tr></table>									Geological Material	From	To (ft.)	Color	Hardness	GRAVEL	0	20	BROWN		CLAY	20	41	BROWN		SAND, LITTLE WATER	41	56			SAND, 20 SLOT	56	63			SAND, 15 SLOT	63	71	BROWN		SAND, 15 SLOT	71	76	GRAY		SAND, FINE	76	80			Casing Type Single casing			Joint
Geological Material	From	To (ft.)	Color	Hardness																																																
GRAVEL	0	20	BROWN																																																	
CLAY	20	41	BROWN																																																	
SAND, LITTLE WATER	41	56																																																		
SAND, 20 SLOT	56	63																																																		
SAND, 15 SLOT	63	71	BROWN																																																	
SAND, 15 SLOT	71	76	GRAY																																																	
SAND, FINE	76	80																																																		
Drive Shoe? Yes ☐ No ☐									Above/Below																																											
Casing Diameter 4 in.									Weight To ft. lbs./ft.																																											
Open Hole From ft. To ft.																																																				
Screen? ☒									Type stainless		Make JOHNSON																																									
Diameter 4 in.									Slot/Gauze 15		Length 5 ft.	Set 71 ft. 76 ft.																																								
Static Water Level 25 ft. land surface									Measure		03/23/2011																																									
Pumping Level (below land surface) ft. hrs. Pumping at									18		g.p.m.																																									
Wellhead Completion Pitless adapter manufacturer									Model																																											
☐ Casing Protection									☐ 12 in. above grade																																											
☐ At-grade (Environmental Wells and Borings ONLY)																																																				
Grouting Information Material bentonite									Well Grouted? ☒ Yes ☐ No ☐ Not Specified		Amount From To ft. 55 ft.																																									
Nearest Known Source of Contamination 90 feet North Direction									Sewer Type																																											
Well disinfected upon completion?									☒ Yes ☐ No																																											
Pump ☐ Not Installed									Date Installed																																											
Manufacturer's name SCHAEFER																																																				
Model Number									HP 0.5	Volt 230																																										
Length of drop pipe 40 ft									Capacity 10	g.p. Typ Submersible																																										
Abandoned Does property have any not in use and not sealed well(s)?									☐ Yes ☒ No																																											
Variance Was a variance granted from the MDH for this well?									☐ Yes ☒ No																																											
Miscellaneous First Bedrock									Aquifer Quat. buried																																											
Last Strat sand									Depth to Bedrock ft																																											
Located by Minnesota Geological Survey																																																				
Locate Method GPS SA Off (averaged) (15 meters)																																																				
System UTM - NAD83, Zone 15, Meters									X 284432	Y 5168344																																										
Unique Number Verification									Site Plan	Input Date 12/15/2017																																										
Angled Drill Hole																																																				
Well Contractor Waskosky Well Drilling									1581		WASKOSKY, T.																																									
Licensee Business									Lic. or Reg. No.		Name of Driller																																									
Remarks																																																				
Minnesota Well Index Report				780770				Printed on 08/13/2026 HE-01205-15																																												