

780782

County Redwood
Quad Delhi
Quad ID 96C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 02/18/2011
Update Date 11/18/2015
Received Date 12/29/2010

Well Name ROBINSON,					Township 113	Range 36	Dir W	Section 35	Subsection ABACDA	Well Depth 524 ft.				Depth Completed 524 ft.				Date Well Completed 12/16/2010			
Elevation 1028					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary				Drill Fluid Bentonite							
Address C/W 31186 349TH ST REDWOOD FALLS MN 56283										Use domestic				Status Active							
Stratigraphy Information Geological Material From To (ft.) Color Hardness TOP 0 1 BLACK SOFT SAND 1 12 TAN SOFT CLAY 12 43 BLUE SOFT GRANITE 43 220 WHT/RED MED-HRD GRANITE 220 524 PINK HARD										Well Hydrofractured? Yes ☐ No ☒				From To							
										Casing Type Single casing				Joint Welded							
										Drive Shoe? Yes ☐ No ☐				Above/Below							
										Casing Diameter 6 in. To 220 ft. 20 lbs./ft.				Hole Diameter 8.7 in. To 246 ft.							
										Open Hole From 220 ft. To 524 ft.											
										Screen? ☐				Type Make							
										Static Water Level 45 ft. land surface Measure 12/16/2010											
										Pumping Level (below land surface) 150 ft. 1 hrs. Pumping at 20 g.p.m.											
										Wellhead Completion Pitless adapter manufacturer MAASS Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)											
										Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To high solids bentonite 15 Sacks 0 ft. 170 ft. bentonite 7 Sacks 170 ft. 240 ft.											
Remarks										Nearest Known Source of Contamination 100 feet Northwes Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No											
										Pump ☐ Not Installed Date Installed 12/16/2010											
										Manufacturer's name SCHAEFER											
										Model Number HP 1 Volt 230											
										Length of drop pipe 200 ft Capacity 10 g.p. Typ Submersible											
										Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No											
										Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No											
										Miscellaneous First Bedrock weathering residuum unc. Aquifer Morton Gneiss Last Strat Morton Gneiss Depth to Bedrock 43 ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 329768 Y 4935695 Unique Number Verification Tag on well Input Date 07/25/2012											
										Angled Drill Hole											
										Well Contractor Peterson Well Drilling, Inc. 2293 HERTLING, E. Licensee Business Lic. or Reg. No. Name of Driller											

Minnesota Well Index Report

780782

Printed on 08/13/2026
HE-01205-15