

Minnesota Unique Well Number

789553

CountyMower
QuadLeroy
Quad ID7D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date05/15/2012
Update Date02/11/2013
Received Date10/29/2012

Well Name	Township	Range	Dir	Section	Subsection	Well Depth	Depth Completed	Date Well Completed					
FARLINGER,	101	14	W	29	DAAACA	320 ft.	320 ft.	05/08/2012					
Elevation	1301	Elev. Method	7.5 minute topographic map (+/- 5 feet)										
Address						Use	domestic	Status	Active				
Well						76001 115TH ST LE ROY MN 55451							
Stratigraphy Information						Well Hydrofractured?	Yes	☐	No	☒	From	To	
Geological Material						Casing Type	Step down		Joint	Welded			
DRIFT						Drive Shoe?	Yes	☒	No	☐	Above/Below		
BROKEN LIMESTONE						Casing Diameter	Weight		Hole Diameter				
LIMESTONE						4 in. To	288 ft.	lbs./ft.	12 in. To 25 ft.				
LIMESTONE						8 in. To	25 ft.	lbs./ft.	8 in. To 288 ft.				
LIMESTONE						4 in. To 320 ft.							
						Open Hole	From	288 ft.	To	320 ft.			
						Screen?	☐	Type	Make				
						Static Water Level							
						35 ft.	land surface		Measure	04/26/2012			
						Pumping Level (below land surface)							
						45 ft.	2 hrs.	Pumping at	15	g.p.m.			
						Wellhead Completion							
						Pitless adapter manufacturer	MONITOR		Model				
						☐ Casing Protection	☐ 12 in. above grade						
						☐ At-grade (Environmental Wells and Borings ONLY)							
						Grouting Information							
						Well Grouted?	☒	Yes	☐	No	☐	Not Specified	
						Material	Amount		From	To			
						neat cement	6	Cubic yards	0	ft.	288	ft.	
						pearock	4.5	Cubic yards	25	ft.	288	ft.	
						Nearest Known Source of Contamination							
						50 feet	Direction		Type				
						Well disinfected upon completion?	☒	Yes	☐	No			
						Pump	☐	Not Installed	Date Installed	05/08/2012			
						Manufacturer's name	GRUNDFOS						
						Model Number	15SQE07-	HP	0.75	Volt	230		
						Length of drop pipe	63	ft	Capacity	15	g.p.	Typ	Submersible
						Abandoned							
						Does property have any not in use and not sealed well(s)?							
						☐ Yes ☒ No							
						Variance							
						Was a variance granted from the MDH for this well?							
						☒ Yes ☐ No							
						Miscellaneous							
						First Bedrock	Upper Cedar Valley		Aquifer	Wapsipinicon/Spil			
						Last Strat	Wapsipinicon/Spillville Fm		Depth to Bedrock	20 ft			
						Located by Minnesota Department of Health							
						Locate Method GPS SA Off (averaged) (15 meters)							
						System	UTM - NAD83, Zone 15, Meters		X	538017	Y	4818827	
						Unique Number Verification	Info/GPS from data		Input Date	04/26/2012			
						Angled Drill Hole							
						Well Contractor							
						Thein Well Rochester, Inc.	2641		KRAUSE, M.				
						Licensee Business		Lic. or Reg. No.		Name of Driller			
Remarks													
VARIANCE TN#4804.													
CASING: REMOVED 8 IN TO 25 FT.													

Minnesota Well Index Report

789553

Printed on 08/13/2026
HE-01205-15