

799024

County Wright
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date05/01/2014
Update Date05/01/2014
Received Date01/24/2014

Well Name EDEL, BRADLEY	Township 121	Range 23	Dir W	Section 21	Subsection ABB	Well Depth 79 ft.	Depth Completed 79 ft.	Date Well Completed 11/01/2013																				
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Bentonite																					
Address C/W 8894 ODEAN AV NE OTSEGO MN 55330						Use domestic	Status Active																					
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SAND/GRAVEL</td><td>0</td><td>50</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>SANDY CLAY</td><td>50</td><td>55</td><td>BRN/RED</td><td>MEDIUM</td></tr><tr><td>GRAVEL/SAND</td><td>55</td><td>79</td><td>VARIED</td><td>MEDIUM</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	SAND/GRAVEL	0	50	BROWN	MEDIUM	SANDY CLAY	50	55	BRN/RED	MEDIUM	GRAVEL/SAND	55	79	VARIED	MEDIUM	Well Hydrofractured? Yes ☐ No ☒ From To		
						Geological Material	From	To (ft.)	Color	Hardness																		
						SAND/GRAVEL	0	50	BROWN	MEDIUM																		
						SANDY CLAY	50	55	BRN/RED	MEDIUM																		
						GRAVEL/SAND	55	79	VARIED	MEDIUM																		
						Casing Type Single casing Joint																						
						Drive Shoe? Yes ☐ No ☒ Above/Below																						
						Casing Diameter Weight Hole Diameter																						
						4 in. To 71 ft. lbs./ft. 8 in. To 50 ft.																						
						6.5 in. To 79 ft.																						
Open Hole From ft. To ft.																												
Screen? ☒ Type stainless Make JOHNSON																												
Diameter Slot/Gauze Length Set																												
2 in. 8 ft. 71 ft. 79 ft.																												
Static Water Level																												
19 ft. land surface Measure 11/01/2013																												
Pumping Level (below land surface)																												
66 ft. 3 hrs. Pumping at 50 g.p.m.																												
Wellhead Completion																												
Pitless adapter manufacturer WHITEWATER Model																												
☐ Casing Protection ☒ 12 in. above grade																												
☐ At-grade (Environmental Wells and Borings ONLY)																												
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																												
Material Amount From To																												
well grouted, type unknown 50 ft. 71 ft.																												
bentonite 4.5 Sacks ft. 50 ft.																												
Nearest Known Source of Contamination																												
125 feet East Direction Septic tank/drain field Type																												
Well disinfected upon completion? ☒ Yes ☐ No																												
Pump ☐ Not Installed Date Installed 11/04/2013																												
Manufacturer's name SCHAFFER																												
Model Number HP 0.75 Volt 230																												
Length of drop pipe 42 ft Capacity g.p. Typ Submersible																												
Abandoned																												
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																												
Variance																												
Was a variance granted from the MDH for this well? ☐ Yes ☒ No																												
Miscellaneous																												
First Bedrock Aquifer																												
Last Strat Depth to Bedrock ft																												
Located by																												
Locate Method																												
System UTM - NAD83, Zone 15, Meters X Y																												
Unique Number Verification Input Date																												
Angled Drill Hole																												
Well Contractor																												
Don Stodola Well Drilling 1691 NEDEGAARD, R.																												
Licensee Business Lic. or Reg. No. Name of Driller																												