

800013

County Wright
Quad Silver
Quad ID 138C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 08/11/2025
Received Date 10/29/2013

Well Name IMHOLTE	Township 122	Range 26	Dir W	Section 32	Subsection DBCBD	Well Depth 140 ft.	Depth Completed 135 ft.	Date Well Completed 07/26/2013																																																							
Elevation 987.5	Elev. Method LiDAR 1m DEM (MNDNR)				Drill Method Non-specified Rotary	Drill Fluid Bentonite																																																									
Address Well B CR CLEAR LAKE MN 55319						Use irrigation	Status Active																																																								
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOPSOIL</td><td>0</td><td>4</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SAND & GRAVEL</td><td>4</td><td>15</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>15</td><td>31</td><td>GRAY</td><td>MED-HRD</td></tr><tr><td>SAND & GRAVEL</td><td>31</td><td>48</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>48</td><td>51</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>SAND & GRAVEL</td><td>51</td><td>73</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>73</td><td>76</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SAND & GRAVEL</td><td>76</td><td>110</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SAND</td><td>110</td><td>135</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>135</td><td>140</td><td>BROWN</td><td>MEDIUM</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	TOPSOIL	0	4	BROWN	SOFT	SAND & GRAVEL	4	15	BROWN	SOFT	CLAY	15	31	GRAY	MED-HRD	SAND & GRAVEL	31	48	BROWN	SOFT	CLAY	48	51	BROWN	MEDIUM	SAND & GRAVEL	51	73	BROWN	SOFT	CLAY	73	76	GRAY	MEDIUM	SAND & GRAVEL	76	110	BROWN	SOFT	SAND	110	135	BROWN	SOFT	CLAY	135	140	BROWN	MEDIUM	Well Hydrofractured? Yes ☐ No ☒ From To		
						Geological Material	From	To (ft.)	Color	Hardness																																																					
						TOPSOIL	0	4	BROWN	SOFT																																																					
						SAND & GRAVEL	4	15	BROWN	SOFT																																																					
						CLAY	15	31	GRAY	MED-HRD																																																					
						SAND & GRAVEL	31	48	BROWN	SOFT																																																					
						CLAY	48	51	BROWN	MEDIUM																																																					
						SAND & GRAVEL	51	73	BROWN	SOFT																																																					
						CLAY	73	76	GRAY	MEDIUM																																																					
						SAND & GRAVEL	76	110	BROWN	SOFT																																																					
SAND	110	135	BROWN	SOFT																																																											
CLAY	135	140	BROWN	MEDIUM																																																											
Casing Type Single casing		Joint																																																													
Drive Shoe? Yes ☐ No ☒ Above/Below																																																															
Casing Diameter 12 in. To		Weight 100 ft. 49.56 lbs./ft.																																																													
		Hole Diameter 18 in. To 140 ft.																																																													
Open Hole <table><tr><td>From</td><td>ft.</td><td>To</td><td>ft.</td></tr><tr><td>Screen? ☒</td><td>Type stainless</td><td>Make JOHNSON</td><td></td></tr><tr><td>Diameter</td><td>Slot/Gauze</td><td>Length</td><td>Set</td></tr><tr><td>12 in.</td><td>45</td><td>35 ft.</td><td>100 ft. 135 ft.</td></tr></table>				From	ft.	To	ft.	Screen? ☒	Type stainless	Make JOHNSON		Diameter	Slot/Gauze	Length	Set	12 in.	45	35 ft.	100 ft. 135 ft.																																												
From	ft.	To	ft.																																																												
Screen? ☒	Type stainless	Make JOHNSON																																																													
Diameter	Slot/Gauze	Length	Set																																																												
12 in.	45	35 ft.	100 ft. 135 ft.																																																												
Static Water Level <table><tr><td>18 ft.</td><td>land surface</td><td>Measure</td><td>07/26/2013</td></tr></table>				18 ft.	land surface	Measure	07/26/2013																																																								
18 ft.	land surface	Measure	07/26/2013																																																												
Pumping Level (below land surface) <table><tr><td>43 ft.</td><td>3 hrs.</td><td>Pumping at</td><td>375 g.p.m.</td></tr></table>				43 ft.	3 hrs.	Pumping at	375 g.p.m.																																																								
43 ft.	3 hrs.	Pumping at	375 g.p.m.																																																												
Wellhead Completion <table><tr><td>Pitless adapter manufacturer</td><td>Model</td></tr><tr><td>☐ Casing Protection</td><td>☒ 12 in. above grade</td></tr><tr><td colspan="2">☐ At-grade (Environmental Wells and Borings ONLY)</td></tr></table>				Pitless adapter manufacturer	Model	☐ Casing Protection	☒ 12 in. above grade	☐ At-grade (Environmental Wells and Borings ONLY)																																																							
Pitless adapter manufacturer	Model																																																														
☐ Casing Protection	☒ 12 in. above grade																																																														
☐ At-grade (Environmental Wells and Borings ONLY)																																																															
Grouting Information <table><tr><td>Well Grouted?</td><td>☒ Yes</td><td>☐ No</td><td>☐ Not Specified</td></tr><tr><td>Material</td><td>Amount</td><td>From</td><td>To</td></tr><tr><td>bentonite</td><td>28 Sacks</td><td>ft.</td><td>50 ft.</td></tr></table>				Well Grouted?	☒ Yes	☐ No	☐ Not Specified	Material	Amount	From	To	bentonite	28 Sacks	ft.	50 ft.																																																
Well Grouted?	☒ Yes	☐ No	☐ Not Specified																																																												
Material	Amount	From	To																																																												
bentonite	28 Sacks	ft.	50 ft.																																																												
Nearest Known Source of Contamination <table><tr><td>1500 feet</td><td>North Direction</td><td>Barnyard Type</td></tr><tr><td colspan="2">Well disinfected upon completion?</td><td>☒ Yes ☐ No</td></tr></table>				1500 feet	North Direction	Barnyard Type	Well disinfected upon completion?		☒ Yes ☐ No																																																						
1500 feet	North Direction	Barnyard Type																																																													
Well disinfected upon completion?		☒ Yes ☐ No																																																													
Pump ☒ Not Installed Date Installed <table><tr><td>Manufacturer's name</td><td>HP</td><td>Volt</td></tr><tr><td>Model Number</td><td>ft</td><td>Capacity</td></tr><tr><td>Length of drop pipe</td><td>g.p.</td><td>Typ</td></tr></table>				Manufacturer's name	HP	Volt	Model Number	ft	Capacity	Length of drop pipe	g.p.	Typ																																																			
Manufacturer's name	HP	Volt																																																													
Model Number	ft	Capacity																																																													
Length of drop pipe	g.p.	Typ																																																													
Abandoned <table><tr><td>Does property have any not in use and not sealed well(s)?</td><td>☐ Yes ☒ No</td></tr></table>				Does property have any not in use and not sealed well(s)?	☐ Yes ☒ No																																																										
Does property have any not in use and not sealed well(s)?	☐ Yes ☒ No																																																														
Variance <table><tr><td>Was a variance granted from the MDH for this well?</td><td>☐ Yes ☒ No</td></tr></table>				Was a variance granted from the MDH for this well?	☐ Yes ☒ No																																																										
Was a variance granted from the MDH for this well?	☐ Yes ☒ No																																																														
Miscellaneous <table><tr><td>First Bedrock</td><td>Aquifer</td></tr><tr><td>Last Strat</td><td>Depth to Bedrock</td></tr><tr><td>Located by</td><td>Minnesota Geological Survey</td></tr><tr><td>Locate Method</td><td>Digitization (Screen) - Map (1:24,000) (15 meters or</td></tr><tr><td>System</td><td>UTM - NAD83, Zone 15, Meters</td></tr><tr><td>Unique Number Verification</td><td>Info/GPS from data</td></tr><tr><td></td><td>Input Date 08/11/2025</td></tr></table>				First Bedrock	Aquifer	Last Strat	Depth to Bedrock	Located by	Minnesota Geological Survey	Locate Method	Digitization (Screen) - Map (1:24,000) (15 meters or	System	UTM - NAD83, Zone 15, Meters	Unique Number Verification	Info/GPS from data		Input Date 08/11/2025																																														
First Bedrock	Aquifer																																																														
Last Strat	Depth to Bedrock																																																														
Located by	Minnesota Geological Survey																																																														
Locate Method	Digitization (Screen) - Map (1:24,000) (15 meters or																																																														
System	UTM - NAD83, Zone 15, Meters																																																														
Unique Number Verification	Info/GPS from data																																																														
	Input Date 08/11/2025																																																														
Angled Drill Hole																																																															
Well Contractor <table><tr><td>Mark J Traut Wells, Inc.</td><td>1404</td><td>ROBBIE/BRUCE</td></tr><tr><td>Licensee Business</td><td>Lic. or Reg. No.</td><td>Name of Driller</td></tr></table>				Mark J Traut Wells, Inc.	1404	ROBBIE/BRUCE	Licensee Business	Lic. or Reg. No.	Name of Driller																																																						
Mark J Traut Wells, Inc.	1404	ROBBIE/BRUCE																																																													
Licensee Business	Lic. or Reg. No.	Name of Driller																																																													