

800555

County Clay
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 02/14/2014
Update Date 02/14/2014
Received Date 01/15/2014

Well Name ROGERS,	Township 137	Range 45	Dir W	Section 5	Subsection ADD	Well Depth 220 ft.	Depth Completed 220 ft.	Date Well Completed 11/11/2013
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Water	
Address						Use irrigation	Status Active	
Contact 2624 110TH ST BARNESVILLE MN 56514						Well Hydrofractured? Yes ☐ No ☐ From To		
Well NA BARNESVILLE MN 56514						Casing Type Single casing Joint		
Stratigraphy Information						Drive Shoe? Yes ☐ No ☐ Above/Below		
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter Weight		
TOP SOIL		0	1			12 in. To 200 ft. lbs./ft.		
SAND		1	15	BROWN				
SAND		15	45	GRAY				
SANDY TILL		45	65					
TILL		65	187					
FINE SAND		187	200					
SAND & GRAVEL		200	220					
Open Hole						From	ft.	To ft.
Screen? ☒						Type stainless	Make	
Diameter						Slot/Gauze	Length	Set
12 in.						100	20 ft.	200 ft. 220 ft.
Static Water Level								
19.3 ft.						null	Measure	11/11/2013
Pumping Level (below land surface)								
19 ft.						33 hrs.	Pumping at	700 g.p.m.
Wellhead Completion								
Pitless adapter manufacturer						Model		
☐ Casing Protection						☒ 12 in. above grade		
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information						Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
Material						Amount	From	To
bentonite						29 Sacks	ft.	70 ft.
Nearest Known Source of Contamination								
feet						Direction	Type	
Well disinfected upon completion?						☒ Yes ☐ No		
Pump ☐ Not Installed						Date Installed	11/26/2013	
Manufacturer's name						GRUNDFOS		
Model Number						800S750-3	HP	75 Volt 460
Length of drop pipe						210 ft	Capacity	800 g.p. Typ Submersible
Abandoned								
Does property have any not in use and not sealed well(s)?						☐ Yes ☒ No		
Variance								
Was a variance granted from the MDH for this well?						☐ Yes ☒ No		
Miscellaneous								
First Bedrock						Aquifer		
Last Strat						Depth to Bedrock ft		
Located by								
Locate Method								
System						UTM - NAD83, Zone 15, Meters	X	Y
Unique Number Verification						Input Date		
Angled Drill Hole								
Well Contractor								
Lako Drilling, Inc.						1644	LAKO, A.	
Licensee Business						Lic. or Reg. No.	Name of Driller	
Minnesota Well Index Report					800555	Printed on 10/02/2026 HE-01205-15		