

Minnesota Unique Well Number

806236

County Benton

Quad

Quad ID

MINNESOTA DEPARTMENT OF HEALTH

WELL AND BORING REPORT

Minnesota Statutes Chapter 1031

Entry Date

02/17/2015

Update Date

02/17/2015

Received Date

11/14/2014

Well Name	Township	Range	Dir	Section	Subsection	Well Depth	Depth Completed	Date Well Completed			
RIPPLINGER,	37	28	W	13	DDC	38 ft.	38 ft.	10/10/2014			
Elevation	Elev. Method					Drill Method	Non-specified Rotary	Drill Fluid	Qwik gel		
Address						Use	domestic	Status	Active		
						Well Hydrofractured?	Yes	☐	No	☒	From
C/W						Casing Type	Single casing	Joint	Glued		
						Drive Shoe?	Yes	☐	No	☒	Above/Below
Stratigraphy Information						Casing Diameter	Weight	Hole Diameter			
						Geological Material	From	To (ft.)	Color	Hardness	4 in.
						CLAY/GRAVEL	0	20	BROWN	SOFT	
						CLAY/GRAVEL	20	33	BROWN	HARD	
						SAND	33	38	BROWN	SOFT	
						Open Hole	From	ft.	To	ft.	
						Screen?	☒	Type	stainless	Make	JOHNSON
						Diameter	Slot/Gauze	Length	Set		
						2 in.	12	4 ft.	33 ft.	38 ft.	
						Static Water Level					
						4 ft.	land surface	Measure	10/10/2014		
						Pumping Level (below land surface)					
						ft.	1 hrs.	Pumping at	40	g.p.m.	
						Wellhead Completion					
						Pitless adapter manufacturer	AQUASEAL	Model	T4-1		
						☐ Casing Protection	☒ 12 in. above grade				
						☐ At-grade (Environmental Wells and Borings ONLY)					
						Grouting Information	Well Grouted?	☒ Yes	☐ No	☐ Not Specified	
						Material	Amount	From	To		
						high solids bentonite	2 Sacks	ft.	32	ft.	
						Nearest Known Source of Contamination					
						100 feet	East Direction	Septic tank/drain field	Type		
						Well disinfected upon completion?	☒ Yes	☐ No			
						Pump	☐ Not Installed	Date Installed	10/10/2014		
						Manufacturer's name	GOULDS				
						Model Number	10LS05	HP	0.5	Volt	230
						Length of drop pipe	20	ft	Capacity	10	g.p.
						Abandoned					
						Does property have any not in use and not sealed well(s)?	☐ Yes	☒ No			
						Variance					
						Was a variance granted from the MDH for this well?	☐ Yes	☒ No			
						Miscellaneous					
						First Bedrock	Aquifer				
						Last Strat	Depth to Bedrock		ft		
						Located by					
						Locate Method					
						System	UTM - NAD83, Zone 15, Meters	X	Y		
						Unique Number Verification		Input Date			
						Angled Drill Hole					
						Well Contractor					
						Able Well, Inc.	1377	BECKWORTH, D.			
						Licensee Business	Lic. or Reg. No.	Name of Driller			
Minnesota Well Index Report						806236	Printed on 08/13/2026				
							HE-01205-15				