

812173

County Le Sueur
Quad Le Center
Quad ID 73B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 10/17/2024
Update Date 03/13/2025
Received Date 08/28/2015

Well Name DOMIJE, JEFF +					Township 111		Range 24		Dir Section W 1		Subsection BBCCAC	
Elevation 1030		Elev. Method LiDAR 1m DEM (MNDNR)										
Address Well 34223 201ST AV MONTGOMERY MN 56069 Contact 1471 LANGFORD TR NEW PRAGUE MN 56071												
Stratigraphy Information												
Geological Material		From	To (ft.)	Color	Hardness							
CLAY		0	26	BROWN	SOFT							
CLAY		26	108	BLUE	SOFT							
CLAY + SAND LAYER		108	162	BLUE	MEDIUM							
SHALE		162	222	GREEN	MEDIUM							
SHALE		222	234	GREEN	SOFT							
SANDROCK		234	300	YEL/WHT	M.HARD							
Well Depth 300 ft.												
Depth Completed 300 ft.												
Date Well Completed 08/13/2015												
Drill Method Non-specified Rotary												
Drill Fluid Water												
Use domestic												
Status Active												
Well Hydrofractured? Yes ☐ No ☒ From To												
Casing Type Single casing												
Joint Threaded												
Drive Shoe? Yes ☒ No ☐ Above/Below												
Casing Diameter 4 in. To 244 ft. 11 lbs./ft.												
Weight												
Hole Diameter 8.5 in. To 244 ft. 4 in. To 300 ft.												
Open Hole From 244 ft. To 300 ft.												
Screen? ☐ Type Make												
Static Water Level 181 ft. land surface Measure 08/11/2015												
Pumping Level (below land surface) ft. hrs. Pumping at g.p.m.												
Wellhead Completion												
Pitless adapter manufacturer MONITOR Model												
☐ Casing Protection ☐ 12 in. above grade												
☐ At-grade (Environmental Wells and Borings ONLY)												
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified												
Material Amount From To												
neat cement 1 Cubic yards 150 ft. 244 ft.												
bentonite 12 Sacks ft. 150 ft.												
Nearest Known Source of Contamination												
81 feet Southeast Direction Septic tank/drain field Type												
Well disinfected upon completion? ☒ Yes ☐ No												
Pump ☐ Not Installed Date Installed 08/13/2015												
Manufacturer's name GOULDS												
Model Number 18-GS-20 HP 2 Volt 230												
Length of drop pipe 216 ft Capacity 18 g.p. Typ Submersible												
Abandoned												
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No												
Variance												
Was a variance granted from the MDH for this well? ☐ Yes ☒ No												
Miscellaneous												
First Bedrock Aquifer												
Last Strat Depth to Bedrock ft												
Located by Minnesota Geological Survey												
Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or												
System UTM - NAD83, Zone 15, Meters X 447045 Y 4922502												
Unique Number Verification Address verification Input Date 03/13/2025												
Angled Drill Hole												
Well Contractor												
Hartmann Well Co., LLP 1622 HARTMANN, K												
Licensee Business Lic. or Reg. No. Name of Driller												
Remarks LAST LINE OF MATERIALS GRID READS: PARCEL#08-001-0300												