

817456

County Otter Tail
Quad Perham
Quad ID 237D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 09/17/2018
Received Date

Well Name RASMASSEN, Elevation 1372 Address Well 209 FOX RUN PERHAM MN 56573 Contact PO BOX 52 GLENWOOD CITY WI 54013 Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND 0 100 BROWN MEDIUM CLAY 100 122 BLUE MEDIUM CLAY 122 124 BLUE SOFT SAND & CLAY STRIPS 124 131 GRAY SOFT SAND 131 139 GRAY SOFT	Township 136 Range 39 Dir W Section 10 Subsection ABADCA Elev. Method LiDAR 1m DEM (MNDNR)	Well Depth 139 ft. Depth Completed 138 ft. Date Well Completed 12/04/2015 Drill Method Non-specified Rotary Drill Fluid Bentonite Use domestic Status Active Well Hydrofractured? Yes ☐ No ☒ From To Casing Type Single casing Joint Glued Drive Shoe? Yes ☐ No ☐ Above/Below Casing Diameter 4 in. To 133 ft. lbs./ft. Weight Hole Diameter 6.7 in. To 23 ft. 6.5 in. To 139 ft. Open Hole From ft. To ft. Screen? ☒ Type stainless Make JOHNSON Diameter 3.7 in. Slot/Gauze 18 Length 5 ft. Set 133 ft. 138 ft. Static Water Level 33 ft. land surface Measure 11/24/2015 Pumping Level (below land surface) 100 ft. 1 hrs. Pumping at 100 g.p.m. Wellhead Completion Pitless adapter manufacturer MONITOR Model BULLDOG ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 4 Sacks ft. 50 ft. Nearest Known Source of Contamination 70 feet Northwest Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No Pump ☐ Not Installed Date Installed 12/04/2015 Manufacturer's name GRUNDFOS Model Number 22SQE10- HP 1 Volt 230 Length of drop pipe 80 ft Capacity 22 g.p. Typ Submersible Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-gray Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 302380 Y 5165410 Unique Number Verification Site Plan Input Date 12/15/2017 Angled Drill Hole Well Contractor Ray Cichy and Sons Well Co. 1654 CICHY, R. Licensee Business Lic. or Reg. No. Name of Driller	
Minnesota Well Index Report		817456	Printed on 08/13/2026 HE-01205-15